

## 3M™ Protecta® Shock Absorbing Lanyard with Rope Single Leg - 140 kg Capacity

**Product Type: Lanyard Part Number: 1260331** 

## **Description**

Sub-brand:	Protecta®
Industry:	Various
Applications:	Various

## Features

reatures	
Lanyard:	<ul><li>Type: Fall Arrest</li><li>Leg Type: Single Rope Leg</li><li>Material: Polyamid / Polyester</li></ul>
Connector-A:	<ul> <li>Type: Snap Hook</li> <li>Locking: Self-Locking</li> <li>Breaking Strength: 22 kN</li> <li>Opening: 19 mm</li> <li>Material: Steel - Zinc Plated</li> </ul>
Connector-B:	<ul> <li>Type: Scaffold Hook</li> <li>Locking: Self-Locking</li> <li>Breaking Strength: 23 kN</li> <li>Opening: 50 mm</li> <li>Material: Steel - Zinc Plated</li> </ul>
Length:	2 m
Weight Capacity:	<ul><li>Min: 50 kg</li><li>Max: 140 kg</li><li>Maximum Peak Force*: &lt;6 kN</li></ul>
Net Weight:	0.8 kg
Operating Temperature:	-35°C +57°C
Standards:	CE EN355:2002

CE EN355:2002

<sup>\*</sup>Tested using standard EN 355 across weight capacity.





## **Important Notice**

The mounting and use of the product described within this document assumes that the user has previous experience of this type of product and that is will be assembled by a competent professional according to product documentation. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M Group (who cannot verify or control these elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for products are determined with the sales contract documents and with the mandatory and applicable law, excluding any other warranty or compensation.



