

Ref.2131 DYNATWO

ROPE ACCESS TREE CLIMBING

Double leg positioning lanyards constructed from 11 mm dynamic rope that can absorb limited shocks that might be produced during positioning activities.

The Dynatwo is the perfect connection lanyard for technical activities like rope access.

The two legs are connected with a single aluminum alloy ring to guarantee full strength (22 kN) in all directions.

Versions without connectors are supplied with rubber keepers to help prevent rotation of the connectors.

Sewn terminations are protected by a durable plastic sheath.

Forged aluminium alloy rings.
Strength >22 kN

Ø11 mm dynamic rope, polyamide
Dynamic elongation 34.9 %

Anti-rotation rubbers

Ref.213101
30-60 cm

Protective thermoshrinkable layer

CE label including individual serial number.

Automatic triple-layer stitchings.
Breaking strength >22 kN



DYNAMIC PERFORMANCE		
Length of lanyard: 100 cm Test mass: 100 kg		
Model	Peak force Free fall 0.6 m (Work positioning limit)	Peak force Free fall 1 m (Fall factor 1)
Static lanyard D=10.5 mm	7.2 kN	14.5 kN
Dynatwo	5.2 kN	8.5 kN

The only scope of this chart is to compare dynamic performance of the two models.
Do not use any EN 354 lanyard for fall-arrest purposes without connecting it to a EN 355 energy absorber.



(Connectors supplied separately)

Ref.	Product name Nombre del producto	Weight Peso		CE EN 354	EAC
		g	oz		
213101	DYNATWO 30-60 cm	170	6.0	•	•
213102	DYNATWO 40-70 cm + 2x0995	410	14.5	•	•