

BLIN KIT

CAMP
Safety
TM ®

FALL
ARRESTER

CE

EN 353-2

CNB/P/11.075

ERC
TP,TC
019/2011



2565 BLIN KIT

TOWERS/INDUSTRY ROOFS CONSTRUCTION

A closed-system fall arrest kit designed to deliver maximum safety and performance. Suitable for both vertical and horizontal/inclined use (also certified for use over sharp edges $r \geq 0.5$ mm). The fall arrest device cannot be removed from the rope to help prevent installation errors. The innovative cam creates smooth action on the rope whether it is being used to ascend or descend the line. Performance on vertical lines can be further increased by using the patented Rope Surfer on the connection lanyards. Wear and tear on the rope is reduced to the minimum thanks to the specially designed locking mechanism that lowers the force transferred to the body in the event of a fall and locks the rope along a long axis, rather than pinching it aggressively with a toothed cam. Hot forged stainless steel locking components combine with a robust aluminum alloy body for exceptional durability over time. Pre-equipped with robust Iridium 10.5 mm semi-static rope with stitched loops on the ends. Available in a variety of lengths. Replacement rope kits are available.


Available with three connections:

- steel oval locking carabiner;
- 26 cm webbing lanyard (total length 42 cm, including the carabiner and the quick link);
- 40 cm webbing lanyard (total length 56 cm, including the carabiner and the quick link).

Certified for a maximum user weight of 120 kg (for vertical use) or 100 kg (for horizontal/inclined use).



256501 - 10 m 256503 - 10 m 256505 - 10 m
 256502 - 20 m 256504 - 20 m 256506 - 20 m



Ref.	Product name Nombre del producto	Weight Peso		Breaking load Carga de rotura	Rope diameter Diámetro de cuerda	CE	 CNB/P/11.075	EAC
		g	oz					
256501	BLIN KIT 10 m + 0981	1110	39.2	15	10.5	EN 353-2	•	•
256502	BLIN KIT 20 m + 0981	1820	64.2					
256503	BLIN KIT 10 m + 0934 + 2030026F + 0981	1240	43.8					
256504	BLIN KIT 20 m + 0934 + 2030026F + 0981	1950	68.8					
256505	BLIN KIT 10 m + 0934 + 2030040F + 0981	1250	44.1					
256506	BLIN KIT 20 m + 0934 + 2030040F + 0981	1960	69.2					



256501 - 10 m
256502 - 20 m



256503 - 10 m
256504 - 20 m



256505 - 10 m
256506 - 20 m

BLIN KIT

- ① Fall arrest device cannot be removed from the rope to help prevent installation errors. Aluminium alloy structure and mechanical parts made by stainless steel.
- ② Strong Iridium 10.5 mm semi-static rope. Made with twisted yarn, which improve abrasion, resistance and durability of the rope. Available in 10 and 20 meters.
- ③ Stitched loop to be connected to the anchor point.
- ④ CE marking with batch and serial number.
- ⑤ Ref..256501 e 256502 supplied with connector ref.0981: steel oval connector with screw gate. The ideal kit to limit height of fall in vertical applications.
- ⑥ Ref.256503 e 256504 supplied with quick link (ref.0934) + webbing lanyard of 26 cm (ref.2030026F) + oval connector (ref.0981). The most versatile configuration for both vertical and horizontal applications.
- ⑦ Ref.256505 e 256506 supplied with quick link (ref.0934) + webbing lanyard of 40 cm (ref.2030040F) + oval connector (ref.0981). This kit gives the optimal freedom of movements for horizontal/inclined use.
- ⑧ "Rope Surfer" is an innovative component that allows to increase the smooth action of the "Blin" on the rope. It is conceived to guide the rope into the device. In the event of a fall, "Rope Surfer" automatically detaches from the rope and the "Blin" arrests the fall immediately.

Available replacement rope kits

Spare rope kits for the Blin Kit. For replacement, cut the old rope and remove from the device, then insert the new rope into the device in the correct direction. Then tie an end knot on the lower end and apply the thermoshrink wrap supplied with the kit.

Ref.	Weight Peso	
	g	oz
25650101 - 10 m	720	25.4
25650201 - 20 m	1430	50.5

