

7040202 SHOCK ABSORBER LIMITED REWIND

Shock Absorber Limited Ref.3029



HORAI Ref.2128

Hot forged, aluminium alloy.

Breaking load 28 kN

Opening 27 mm

Fall arrest lanyards equipped with the Shock Absorber Limited (ref.3029) for work in areas that are closer to the ground or where clearance is limited.

Constructed from 32 mm polyamide webbing with rewind elastic sewn in to automatically contract the length of the lanyard.

HMS BELAY LOCK Ref.1176

Screwgate, aluminium alloy.

Breaking load 23 kN

Opening 24 mm

TOWERS/INDUSTRY CONSTRUCTION

Maximum extension: High strength Fall factor 1 = 50 cm polyamide stitching. Fall factor 2 = 70 cmCE label with Batch Breaking load 22kN Maximum peak force: and individual Serial <6 kN (4.5-5.5 kN approx.) Number included. Patented anti-rotation lever. Polyamide with stainless steel core. 2128 105-150 cm

Polyamide tubolar webbing.

Width 32 mm

Elastic tape inside.

Ref.	Product name Nombre del producto	Weight Peso		(€
		g	oz	EN 355
7040202	SHOCK ABSORBER LIMITED REWIND DOUBLE 105-150 cm + 1176 + 2x2128	620	21.9	•