

IMPORTANT INFORMATION - PLEASE READ AND SAVE



Made in USA of US and foreign components

REPAIR

All repair work shall be performed by the manufacturer. All other work or modifications void the warranty and releases CMC from all liability and responsibility as the manufacturer.

SAMPLE INSPECTION AND MAINTENANCE LOG

The sample log suggests records that should be maintained by the purchaser or user of life safety equipment.

Equipment Inspection and Maintenance Log table with columns: Date, How Used or Maintained, Comments, Name. Includes fields for Item #, Date in Service, Brand/Model, and Strength.

WARNING

- SERIOUS INJURY OR DEATH MAY RESULT FROM THE IMPROPER USE OF THIS EQUIPMENT. THIS EQUIPMENT HAS BEEN DESIGNED AND MANUFACTURED FOR USE BY EXPERIENCED PROFESSIONALS ONLY. DO NOT ATTEMPT TO USE THIS EQUIPMENT WITHOUT PRIOR TRAINING. THOROUGHLY READ AND UNDERSTAND ALL LABELS AND INSTRUCTIONS BEFORE USE. USE, INSPECT AND REPAIR ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.



MEETS THE BELT REQUIREMENTS OF NFPA 1983, STANDARD ON LIFE SAFETY ROPE AND EQUIPMENT FOR EMERGENCY SERVICES, 2017 EDITION, AND THE OPTIONAL FLAME RESISTANCE REQUIREMENTS OF NFPA 1983, TYPE ESCAPE.

EMERGENCY SERVICES BELT IN ACCORDANCE WITH NFPA 1983 - 2017.

CMC Rescue, Inc.

6740 Cortona Drive, Goleta CA 93117 USA 805-562-9120 / 800-235-5741 cmcpro.com

ISO 9001 Certified

©2018 CMC Control No. 20330X.02.012418

USER INFORMATION

User Information shall be provided to the user of the product. NFPA Standard 1983 recommends separating the User Information from the equipment and retaining the information in a permanent record.

Additional information regarding auxiliary equipment can be found in NFPA 1500, Standard on Fire Department Occupational Safety and Health Programs, and NFPA 1983, Standard on Life Safety Rope and Equipment for Emergency Services.

INSPECTION

Inspect the equipment according to your department's policy for inspecting life safety equipment. Inspect the equipment prior to entry into service, after each use, and at least once every 12 months.

When inspecting the equipment, check the webbing and rope for cuts, worn or frayed areas, broken fibers, soft or hard spots, discoloration, or melted fibers. Check the stitching for pulled threads, abrasion, or breaks.

The service life of equipment depends greatly on the type of use and the environment of use. Because these factors vary greatly, a precise service life of the equipment cannot be provided.

PUTTING ON YOUR BELT

The belt should be wrapped over your turnout coat and around your waist. After securing the snap buckle, the D-ring attachment point should be located directly in front of you.

USING YOUR BELT

Rappel / escape devices should be connected to the D-ring with a locking carabiner.

- To prevent roll-out, use only locking carabiners. This belt should only be used for temporary suspension during emergency rappel / escape situations. This belt is not intended to provide the same support or safety as a life safety harness.

CARRYING, MAINTENANCE & STORAGE

During use, carrying and storage keep the equipment away from acids, alkalis, exhaust emissions, rust and strong chemicals. Do not expose the equipment to flame or high temperatures.

If the equipment becomes soiled, it can be washed in cold water with a mild detergent that is safe for use with nylon and polyester. Dry out of direct sunlight. Do not dry in an automatic dryer.