

PROTECH™ PULLEYS



Ideal for mountain rescue, swift water, ski patrol, tower work or other technical uses, where equipment weight is a significant consideration, these lightweight, full-strength Prusik-minding pulleys feature extremely low-profile stainless steel hardware to reduce snagging on rocks, roots, and uneven surfaces. By machining the side plates, the thickness of the metal can be optimized to maximize the strength-to-weight ratio, a process that cannot be done with the traditional bent metal side plates. The unique axle assembly delivers a smooth side plate and impressive strength. The aluminum sheave is mounted on sealed ball bearings for high efficiency. Ideal for small block-and-tackle kits.

Note: Not compatible with 1/2-in (12.5-mm) or larger ropes.

Do not load a single side only of a double sheave pulley.

Option	Single
Item	300501
PRODUCT WEIGHT	3.3 OZ (94 G)
SHEAVE TREAD SIZE	1 X 7/16 IN (25 X 11 MM)
TYPE	SINGLE
COLOR	SAND
NFPA RATING	GENERAL USE
3 SIGMA MBS	36 KN (8,093 LBF)
Price	\$69
Option	Double
Item	300502
PRODUCT WEIGHT	5.5 OZ (156 G)
SHEAVE TREAD SIZE	1 X 7/16 IN (25 X 11 MM)
TYPE	DOUBLE
COLOR	SAND
NFPA RATING	GENERAL USE
3 SIGMA MBS	37 KN (8,318 LBF)
Price	\$106