

D-RING 2 HOLE ANCHOR PLATE

ANCHORAGE CONNECTOR

FEATURES & BENEFITS

- Compatible with Horizontal Lifelines
- Large D-ring
- For temporary or permanent installations
- Easy to install
- Plate size: 2" x 4 1/4"
- Bolt or weld to structure



PLATE

Made from stainless steel

BOLT HOLES

For metal or concrete installations

D-RING

Made of durable zinc-plated steel

SHOWN:
PART #00360

SPECIFICATIONS

STANDARDS:

OSHA 1926 Subpart M & 1910
ANSI Z359.18-17 & A10.32-12
Type A Anchorage Connector

MATERIALS:

Stainless steel and Zinc-plated steel

WORKER CAPACITY:

130 - 420 lbs.

PERFORMANCE:

- Maximum Users: 1
- 5,000 lb. MBS (Minimum Breaking Strength)

NOTES:

- Minimum service temperature: -30°F
- Minimum substrate requirements:
 - Wood: Do not install.
 - Metal: 1/4"
 - Concrete: 4 1/2"

APPLICATIONS



- **PERSONAL FALL ARREST:**

D-Ring 2 Hole Anchors may be used in Personal Fall Arrest applications to support:

- MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
- Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use.
- Applicable D-rings: Dorsal.



- **RESTRAINT:**

D-Ring 2 Hole Anchors may be used in Restraint applications.

- **RESCUE/CONFINED SPACE:**

D-Ring 2 Hole Anchors may be used in Rescue/Confined Space applications.

- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of lanyard / SRL.
- Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No free fall is permitted.
- Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, Shoulder.



- **WORK POSITIONING:**

D-Ring 2 Hole Anchors may be used in Work Positioning applications.

- Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands.
- Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs.
- Maximum allowable free fall is 2'.
- Applicable D-rings: Side & Shoulder.



- **RESCUE/CONFINED SPACE:**

D-Ring 2 Hole Anchors may be used in Rescue/Confined Space applications.

- Rescue systems function to safely recover a worker from a confined location or after exposed to a fall.
- Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs.
- No free fall is permitted.
- Applicable D-rings: Dorsal, Chest, & Shoulder.



NEED MORE INFORMATION?

P: 1.800.466.6385 | VISIT OUR WEBSITE: GUARDIANFALL.COM