

## DIABLO SRL 2.0

SELF-RETRACTING LIFELINE

### FEATURES & BENEFITS

- The premier mini-retractable on the market
- Six bolts secure housing
- Supremely portable and lightweight
- Multiple hook configurations available
- Improved roller guide reduces web abrasion
- Shock pack cover protects webbing from weather and contaminants



SHOWN:  
**PART #11080**

#### CARABINER

Double-locking carabiner with 3,600 lb. strength gate

#### SWIVEL TOP

Allows SRL to swivel on its axis

#### STURDY HOUSING

6 bolts secure housing

#### ROLLING GUIDE

Reduces web abrasion

#### SHOCK PACK COVER

Protects webbing from weather and contaminants

#### SHOCK PACK

Absorbs arrest forces in the event of a fall

#### SNAP HOOK

Several different types available (see next page)



SHOWN:  
**PART #11087**

### SPECIFICATIONS

#### STANDARDS:

OSHA 1926 Subpart M & 1910  
ANSI Z359.14-14 & A10.32-12

#### MATERIALS:

Polyester, Stainless Steel  
Aluminum, & Nylon

#### WORKER CAPACITY:

130 - 420 lbs.

#### PERFORMANCE:

- Average Arrest Force: 1,350 lbs.
- Maximum Arrest Force: 1,800 lbs.
- Maximum Deceleration Distance (for non-LE applications): 24"
- Maximum Users: 1

#### NOTES:

- Class A SRL
- Always maintain 100% tie-off
- Maximum 2' free fall
- For dual leg kit, assemble and use according to instructions provided with dual SRL bracket
- If using with rebar hook configuration, Diablo must always be worn at harness dorsal D-ring. Rebar hook must ONLY be connected to compatible structural rebar.

| PART # | DESCRIPTION  | WEIGHT   | LENGTH |
|--------|--|----------|--------|
| 11080  | Diablo 6' Web SRL with Steel Snap Hook             | 2 ½ lbs. | 6'     |
| 11081  | Diablo 6' Web SRL with Aluminum Carabiner          | 2 ¼ lbs. | 6'     |
| 11082  | Diablo 6' Web SRL with Aluminum Rebar Hook         | 3 lbs.   | 6'     |
| 11083  | Diablo 6' Web SRL Steel Rebar Hook                 | 3 ½ lbs. | 6'     |
| 11084  | Double Diablo 6' SRL Kit with Steel Snap Hooks     | 5 ¾ lbs. | 6'     |
| 11085  | Double Diablo 6' SRL Kit with Aluminum Carabiners  | 5 ½ lbs. | 6'     |
| 11086  | Double Diablo 6' SRL Kit with Aluminum Rebar Hooks | 6 ¾ lbs. | 6'     |
| 11087  | Double Diablo 6' SRL Kit with Steel Rebar Hooks    | 7 ¾ lbs. | 6'     |

## APPLICATIONS



### PERSONAL FALL ARREST:

Diablo SRLs may be used in Personal Fall Arrest applications to support:

- MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
- Maximum permitted free fall is 2' (SRL may be positioned no more than 2' below harness dorsal D-ring or 2' above anchor point).
- Applicable D-rings: Dorsal.



### RESTRAINT:

Diablo SRLs may be used in Restraint applications. Restraint systems:

- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No free fall is permitted.
- May only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



**NEED MORE INFORMATION?**

P: 1.800.466.6385 | VISIT OUR WEBSITE: [GUARDIANFALL.COM](http://GUARDIANFALL.COM)