

Concrete Swivel Anchor

GUARDIAN
FALL PROTECTION

Part #	Description
00240	Concrete Swivel Anchor D-ring and Bracket Assembly
00241	Concrete Swivel Anchor Bolt HSL-3-B M 12/5
00242	Concrete Swivel Anchor Kit. Includes (1) #00240 & (1) #00241
00243	Concrete Swivel Anchor Bolt (#00241) 5-Pack
00244	Concrete Swivel Anchor Bolt (#00241) 12-Pack



Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.18-17, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable. Contact customer service for details.

Concrete Swivel Anchor is suitable for the following applications:



Personal Fall Arrest: Concrete Swivel Anchors may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Concrete Swivel Anchors may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: Concrete Swivel Anchors may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



Rescue/Confined Space: Concrete Swivel Anchors may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Materials: galvanized steel.

Substrate requirements:

- DO NOT install onto wood, steel, hollow block, grout, or lightweight concrete.
- Concrete MUST be at least 3,000 psi, and at least 6¼" thick.

Required drill bit size: 18mm.

MAXIMUM 1 connection per Concrete Swivel Anchor