

## D-Bolt Forged Anchorage Connector

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not Repairable. Contact customer service for details.



D-Bolt Forged Anchorage Connector is suitable for the following applications:



**Personal Fall Arrest:** D-Bolt Forged Anchorage Connectors may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



**Restraint:** D-Bolt Forged Anchorage Connectors may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**Work Positioning:** D-Bolt Forged Anchorage Connectors may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



**Rescue/Confined Space:** D-Bolt Forged Anchorage Connectors may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, Shoulder.

**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.**



Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: heat-treated alloy steel.

MAXIMUM 1 connection per D-Bolt Forged Anchorage Connector.

UPC-A Codes:

00370: 672421003702

00371: 672421003719

00372: 672421003726

00373: 672421003733

Part #	Bolt Hole Size	Description
00370	1/2"	D-Bolt Forged Anchorage Connector (bolt not included).
00371	5/8"	D-Bolt Forged Anchorage Connector (bolt not included).
00372	3/4"	D-Bolt Forged Anchorage Connector (bolt not included).
00373	9/16"	D-Bolt Forged Anchorage Connector (bolt included).