

Friction Fit Bracket

Part #: 15026

Compliant with all OSHA 1910 & OSHA 1926 Subpart M regulations.

Custom configurations not available. Not repairable.
Contact customer service for details.



Friction Fit Bracket is suitable for the following applications:



Fall Prevention: Friction Fit Bracket may be used in Fall Prevention applications ONLY. Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge, and may be used in substitute of Fall Protection or safety netting systems. Installation requirements for Friction Fit Bracket set forth in this manual MUST be adhered to. Personal Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.



WARNING

Use of equipment in unintended applications may result in serious injury or death. NEVER make any connections to guardrail systems.

Materials: zinc-plated steel.

Surfaces more than 6' above lower levels require the use of a Fall Prevention or Fall Protection system.

Friction Fit Brackets may be placed a MAXIMUM of 8' apart.

Installation location MUST be deemed compatible with Friction Fit Brackets by a Competent Person.

Friction Fit Brackets MUST be installed flush against substrate, and must allow guardrail posts to be positioned perpendicular to work surface.

All guardrail posts, guardrails, and all other equipment must be selected and deemed compatible by a Competent Person. All guardrails MUST be compatible 2" x 4" or 2" x 6" construction grade lumber, or compatible snap-on metal rails.

UPC-A Code: 672421150260.

