

Window Gap Anchor

Part #: 15176

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations not available. Not repairable.
Contact customer service for details.

Window Gap Anchor is suitable for the following applications:



Personal Fall Arrest: Window Gap Anchor may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Window Gap Anchor may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

**For all applications: worker weight capacity range
(including all clothing, tools, and equipment) is 130-420 lbs.**



Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

ONLY for horizontal installations. NEVER install vertically. Window Gap Anchor MUST be installed in a manner where it is supported by the floor or windowsill.

Window Gap Anchor adjusts to fit frames between 24" - 48" wide.

Materials: powder-coated steel
and stainless steel.

MAXIMUM 1 user per Window
Gap Anchor.

UPC-A Code: 672421151762

