

**CORE twin l'yrd - 1.25m no connectors EOL**
**L2B125**
**Basic range of energy absorbing lanyards.**
**Features:**

- Range of connectors and lengths
- Single and twin leg options
- Rated for 125kg users
- Unique serial ID number

Kernmantle rope legs. Twin versions interlocked preventing issues caused by 3 way loading.

Approved for users up to 125 kg.

Absorber will not deploy at force less than 200 kg. Min. strength 1500 kg after deployment.

All products have unique serial ID number allowing easy management of equipment portfolio.

| Code    | Legs | Harness Connector | Length ***cm | Anchorage Connector |
|---------|------|-------------------|--------------|---------------------|
| L2B125  | 2    | None              | 125          | None                |
| L2B150  | 2    | None              | 150          | None                |
| L2B125S | 2    | Delta             | 125          | Scaff hook          |
| L2B***S | 2    | Oval              | 150/175      | Scaff hook          |
| L1B175K | 1    | Oval              | 175          | Twistlock           |
| L1B175S | 1    | Oval              | 175          | Scaff hook          |

\*\*\*denotes length


**Specifications:**

*NB: specifications and colour may change without notice.*

Size: 1.25m

EN Test Mass: 100

Loading: Additionally tested with 125kg.

Conformity: EN354, EN355, EN362

Materials: Polyester / polyamide webbing. Steel and alloy.

Weight (kg): 1.55

Industries: Telecoms, utilities, fire and rescue service, renewables industry.