

## Vector fall arrester

**D23**

**A versatile, multi-functional fall arrest and work positioning rope device designed specifically for roof work and ladder climbing.**

### Features:

- Multi-functional – fall arrest, work positioning
- Can be loaded onto the rope at any point
- Moves freely up and down a vertical line
- Self-locking cam
- Supremely simple to use
- Easy to inspect and maintain – all component parts are visible
- Anodised aluminium and stainless steel construction
- Individually marked for traceability

The Vector is designed for fall arrest when used on a vertical rope and for work restraint when used on level or sloping ground.

Vector can be fitted to the rope at any point. It moves up and down freely with the user but will lock if a load is applied, allowing a high degree of flexibility whilst working.

For maximum ease of movement and safety, we recommend attachment with a short extension link (e.g. 35 cm including connectors).

Satisfies requirements of both EN 353-2 (vertical fall arrest) and EN358 (work positioning) standards.

Inspection and cleaning is simple as all component parts of device are visible and accessible.

Stainless steel friction surfaces for reduced wear and consistent performance.

NB: This device is not designed for two person loads therefore not suitable for rope access.



### Specifications:

*NB: specifications and colour may change without notice.*

Size: 10.5 mm - 11.0 mm rope

EN Test Mass: 125 kg

Loading: 125 kg

Conformity: EN353-2, EN358

Materials: Anodised aluminium and stainless steel construction

Weight (kg): 0.24

Industries: Roof Access, Ladder Climbing