

ELITE twin l'yrd - oval, 1.25m, s.hooks
L2M125S
High load rated energy absorbing lanyards with connector & length options for a range of fall protection applications
Features:

- High load rating, approved for users up to 140kg.
- Large central ring on twin leg versions
- Suspension intolerance relief loops
- Single and twin leg options
- High twist HELIX™ ropes
- Range of connectors and lengths
- Durable protective cover
- Unique serial ID number

Large central ring provides parking point for unused leg and prevents issues caused by 3 way loading.

Absorber will not deploy at force less than 200kg. Min. strength 1500kg after deployment.

Heatshrunk absorber with replaceable cover, tamper evident but with increased durability.

Suspension intolerance relief loop deploys automatically providing support for both feet.

Patented HELIX-™ ropes allow high degree of twist in lanyard legs, minimising kinking.

Unique serial ID number allows easy management of equipment.

Code	Legs	Harness Connector	Length ***cm	Anchorage Connector
L2M***S	2	Oval	125/150/175	Scaff hook
L2T***S	2	TriAct	125/150/160/175	Scaff hook
L2M175DC	2	Oval	175	Pear, step hooks clipback & sleeve
L2T160A	2	TriAct	160	CE/ANSI hook
L2T150B	2	TriAct	150	Steplock hook
L2T170BC	2	TriAct	170	Steplock pear hook, clipback & sleeve
L2T185KC	2	TriAct	185	Twistlock, clipback & sleeve
L1T150P	1	TriAct	150	Pear hook
L1T195K	1	TriAct	195	Twistlock, ring & sleeve

Option: MML04 - Replacement absorber cover


Specifications:

NB: specifications and colour may change without notice.

Size: 1.25m

EN Test Mass: 100

Loading: Additionally tested with 140kg

Conformity: EN354, EN355, EN362

Materials: Polyester / polyamide webbing, alloy.

Weight (kg): 1.55

Industries: Telecoms, utilities, fire and rescue service, renewables industry.