

AXON specialist access harness QC

H20Q

Ergonomic, comfortable Rope Access harness also suitable for all other work at height.

Features:

- Large central waist D-ring configuration allows multiple attachments
- Shoulder, waist and leg pads
- 9 points of adjustment
- Integral delta screwlink for fitting a chest ascender
- Folding side D-Rings
- Multiple tool and accessory attachments
- Quick connect leg buckles

Large waist D-ring with webbing loop allows easy attachment of descenders, ascenders and cows tails. Pivots forward when not loaded to reduce bulk at front of harness. Alloy karabiner connects behind waist D-ring. Hook free gate prevents snagging and reduces potential webbing damage.

Ergonomically contoured pads are shaped and formed for comfort. 3 dimensional forming and plastic inserts provide support where it is needed but allow movement in essential areas.

Quick connect leg loop buckles for quick and easy fitting. Standard buckles allow one handed adjustment with positive locking on chest and waist plus leg loop back straps and rear D-ring.

Integral delta screwlink simplifies attachment and use of chest ascenders. Screwlink can be removed if not required.

Side D-rings allow work positioning attachments and fold away discreetly when not required.

Lightweight, durable gear loops with 20kg rated load and 7:1 factor of safety. Accessories and tool bags can also be attached directly around the waist belt webbing.

Complies with Siemens PPE requirements PRO-13838 Ap1

Options:

- H20QL - Large size. Torso 100-135cm, Waist 80-165cm, Thigh 60-100cm
- H20/H20L - Standard leg loop buckles - standard and large sizes



Specifications:

NB: specifications and colour may change without notice.

Size:	Universal
EN Test Mass:	140kg
Loading:	Fall Arrest & Rescue Loads
Conformity:	EN358, EN361, EN813
Materials:	Polyamide, Mild Steel & Aluminium
Weight (kg):	2.05
Industries:	Rope Access, Oil & Gas

Attachment Points:

Dorsal
Sternal
Lateral
Waist

Harness Measurements (cm):

Torso	95-120
Waist	70-140
Thigh	60-80