



Lyon Small Animal Rescue Bag MK2

LPP0016 MK2

lyon.co.uk/user-instructions



For more detailed user information and to download a PDF copy of these instructions follow the link above or scan the QR code with your smart phone

Lyon Equipment Limited Units 3-7, Tebay Business Park,

Old Tebay,

Cumbria, United Kingdom

CA10 3SS

Tel: +44 (0) 15396 24040

Web: lyon.co.uk

24040 k 5055835614101

© Lyon Equipment 2019

This information to be read and kept in conjunction with the Lyon Rated Bag and General User Instructions.

All users must have appropriate training, knowledge and experience of work and rescue at height, animal care and animal handling, or be working under the direct supervision of such a person.

Note: In these instructions the Small Animal Rescue Bag Mk2 is referred to as 'the Bag'.

The Bag is not a general-purpose equipment bag. Use for movement of other items is the decision of the user and should only be carried out after adequate risk assessment has indicated the product is acceptable for the intended use.

All other uses of this product are forbidden without written approval from Lyon Equipment Ltd.

ANIMAL RESCUES - WARNING

Recovering a frightened animal from an insecure position poses a significant danger to the rescuer from the animal trying to defend itself. The rescuer must carefully risk assess the situation, and avoid risks that could ultimately lead to the rescuer becoming the casualty.

The use of appropriate PPE and mechanical aids (slip leads, rigid leads, graspers etc.) may be necessary to effectively control or restrain the animal.

Do not traverse while trying to catch the animal - remain vertically below the anchor point to minimise the risk of a pendulum fall.

Trapped animals may be injured and can be unpredictable - seek advice from the owner/animal welfare organisation regarding appropriate response. Try to ascertain the animal's name if a domestic pet, size, whether it is likely to be aggressive, medical treatment and evacuation options etc.

Do not leave animals in the Bag for extended periods. Minimise the time in use to the shortest possible to effect a recovery. Monitor the animal throughout the recovery for signs of distress and cease use of the Bag if the animal's condition worsens.

Do not release the Bag from the rescue system during a rescue. Removal increases the risk to the animal and the likelihood of the Bag being dropped.

Nomenclature of parts

- Lifting handles
 Grab handles
- 3 Foot tab
- 4. Side entry door zip
- 5. Side entry door buckles
- 6. Side entry
- 7. Ventilation mesh
- 8. Top entry zip

- Zip securing connector
- 10. Zip securing
- II. Lead access
- 12. Lead clip in
- 13. Storage pocket
- 14. Storage compression straps





how to plan and carry out a small animal -12. rescue. It relates only to the function -11. of the Bag. The Bag is intended to provide the

secure, aerated containment necessary to affect the recovery of a domestic animal weighing no more than 50 kg, within the limits and restrictions defined by these User Instructions. It is not a medical aid, it does not provide a rigid platform or act as a splint.

Both lifting handles of the Bag are attached to the end of the lifting/ lowering line with a suitable locking connector.

Ensure the connector is clipped around the handle section marked in RED and is captivated by the stitched webbing loop below.



Danger - Do not clip around the stitched webbing loop only.

This connection must be correctly orientated, closed and locked.

Where a secondary system is used, attach both lifting handles of the Bag to the end of the safety line with a suitable locking connector, as described above. This connection must be correctly orientated with gates opposed, closed and locked.

Note: The four grab handles on the lower sides, and the two smaller grab handles below the lifting handles, are for steering/manoeuvring only and must not be used for lifting or securing the bag.

In use, the side entry door is the

intended point of access and egress for the animal.

The side entry door has two buckles on the lower corners of the door and a zip with two independent pullers. Always open the door fully before attempting to move the animal into the Bag. The open door may be tucked between the lifting handles to maintain the opening.

A foot tab is provided on the base of the Bag.A foot placed on the tab may assist in holding the Bag secure whilst the zip is pulled open/closed.

The animal may be moved into the Bag in a variety of ways. A lead access slot is provided in the end of the Bag opposite the door. This allows a suitable lead to be pre-placed through the Bag.

As soon as the animal is fully within the Bag, secure the door to prevent the animal escaping. Close the zip first, making sure both zip pullers are at the top, then close the two buckles. To ensure the animal does not open the door zip, clip the two zip pullers together using the attached connector and fasten the connector to the zip securing loop.

The Top Entry zip is not intended as the primary means of loading. It allows access to the animal for viewing/ monitoring as necessary. To ensure the animal does not open the Top Entry zip, clip the two zip pullers together using the attached connector and fasten the connector to the zip securing loop.

If loading via the Top Entry zip, care must be taken not to fully disconnect the Bag from the rescue system. A separate tether, connecting the rescue system to the Bag via the lifting handles may be appropriate. This tether must be of sufficient strength for the loads applied and not interfere with the function of the Bag and the rescue system.

Storage and transport

The Bag is provided with two storage compression straps to allow storage and transport in a compact package.

These straps must not be used for any other purpose.

End of document.

		Lyon Product Inspection Record	spection Reco	rd		
Product code		Product description	Year of manufacture		Purchase date	
Length if applicable		Individual serial number	Date of first use		Certificate of conformity number	
Manufacturer Lyon Equipment Ltd.		Address Address Thus, 37 Takop Business Pank Pennith VACA (19.335	Tel. +44 (0) 15396 24040 Fox. +44 (0) 15396 26330 info@byon.co.uk iyon.co.uk	96 24040 96 26330	Other relevant information	
		Record of inspection and repair	ion and repair			
Date	Comments			Name and signature o	Name and signature of competent inspector	Next due date
EN		All user instructions supplied with this product must be kept as part of the product inspection record	ust be kept as p	art of the product inspe	ection record	





Rated Bags

Lyon Equipment Limited Units 3-7, Tebay Business Park, Old Tebay, Penrith,

Cumbria, United Kingdom

CA10 3SS

Tel: +44 (0) 15396 24040 Email: info@lyon.co.uk

Web: lyon.co.uk

© Lyon Equipment 2018

For more detailed user information and to download a PDF copy of these instructions follow the link above or



ORIGINAL INSTRUCTIONS

Quality assurance

Quality management system assessed and certified as meeting the requirements of ISO 9001.

Working Load Limit

Refer to the front cover of these instructions and markings on the Rated Bag. Please note that the working load limit refers to the total load on the attachment point: the combined weight of the Rated Bag and any accessories must not exceed this amount.

Note: In these instructions the Rated Bag is referred to as 'the Bag'.

WARNING

Make sure that you have read and understood these instructions before using this equipment.

These user instructions must be read and kept along with any other user information supplied with this product.

Where accessories are available refer to the user instructions supplied with the accessories

Activities at height are hazardous and may lead to injury or death. It is the user's responsibility, at all times, to ensure that they understand the correct use of any equipment supplied by or through Lyon Equipment, use it only for the purposes for which it is designed, and practice proper safety procedures.

This product must not be used outside its limitations, or for any purpose other than those described in these user

instructions. Misuses forbidden in these instructions are examples only; many other misuses may exist which could lead to injury or death.

Check compatibility with other elements in the safety chain before using the Bag. The performance of the elements of the safety chain must not be compromised when the Bag is installed and in use.

Please note, the information in these user instructions is not exhaustive, and is not a substitute for comprehensive instruction and training by a competent person.

Lyon Equipment is not responsible for any consequences, whether direct, indirect or accidental, resulting from the use of its products.

If you are unsure about the correct use of this product, please contact us.

Always know the weight of the intended load before using the Bag. Do not overload the Bag.

Always select a Bag of suitable size and shape for the load, to minimise the risk of the load falling out while being lifted or lowered.

Always inspect the Bag before use. Refer to instructions for inspection.

Damage and wear significantly reduce Bag working load limits.

Do not place unprotected objects in the Bag that could cut, pierce or damage the Bag. Tools and sharp objects can cause damage which can affect the strength of the bag. The plastic drum or liner supplied with some models of bag provides additional protection against damage.

A cut, damaged, overloaded or topheavy Bag could release the contents causing damage, injury or death.

When carrying out work at height, maintain an appropriate exclusion zone.

Small objects should be suitably contained within the Bag, to prevent accidental spillage.

Who can use this equipment

This equipment should only be used by trained, competent and responsible persons, or the user should be under the direct supervision of a trained, competent and responsible person.

Activities at height should not be undertaken by persons whilst under the influence of alcohol or drugs, or whilst suffering from diabetes, epilepsy, fits, blackouts, fear of heights, vertigo / dizziness / difficulty with balance, heart disease / chest pain, high or low blood pressure, impaired limb function, obesity, psychiatric illness, musculoskeletal issues, e.g. a bad back.

General instructions for use

Equipment must be checked before each use, to ensure it is serviceable and operates correctly. Checks should also be carried out during use. In addition, a thorough inspection by a competent inspector should be carried out in strict

accordance with these user instructions, and a record kept of these inspections.

The lifting device and anchor points are of primary importance and should be unquestionably reliable. They should be strong enough to withstand the foreseeable maximum load that could be applied with an appropriate factor of safety. Take into account the possibility of the load becoming snagged, and any increase in forces which may result.

When selecting an anchor, the anticipated directions of loading and potential loads should be taken into account.

Anchors should not have sharp or rough edges which could damage equipment (use edge protection if necessary).

Use

This Bag is designed for lifting and lowering loads within the weight limits and restrictions defined by these User Instructions.

Always attach the lifting/lowering system as indicated on the label on the bag. If the bag is supplied with a connector, make sure that it is correctly orientated and fully closed.

All connections and bag closure systems must be checked for correct orientation, closure and locking before the lifting or lowering operation begins.

Always carry out lifting operations in accordance with the Lifting Operations and Lifting Equipment Regulations 1998 (LOLER) or local legislation relating to

lifting operations and lifting equipment in the country of use.

Maintaining your equipment

Detach any accessories, and remove any removable parts, e.g. protective sleeve or plastic drum. Wash in clean water not exceeding 30°C with pure soap and rinse in clean cold water. Do not use chemical products, solvents or detergents – these should be regarded as harmful.

Due to the difficulties in effectively disinfecting equipment, we recommend that any contaminated equipment should be withdrawn from use and disposed of in a suitable manner.

Equipment must be clean and dry before reassembly of components, if applicable, and storing. Always allow to dry naturally, away from direct heat. Equipment should be stored in a cool, dry, well-ventilated area, away from excessive heat, high humidity, sharp edges, corrosives, sunlight or other sources of ultraviolet light (UV) and other possible causes of damage.

After cleaning, the threads of the Maillon Rapide connectors (if supplied) should be lightly oiled.

If necessary, lubricate the hinged gate of any connectors supplied.

Zips (if fitted) can be lubricated using a suitable silicone-based lubricant. Wipe away and excess lubricant.

During transport, this product should be protected from abrasion, mechanical

damage, chemical contamination, UV and heat.

Textiles

Always keep textile items at temperatures between -30°C and +50°C.

Metal items

Always keep metal items at temperatures between -20°C and +60°C.

No alterations, additions or repairs may be made to this product without the manufacturer's prior written consent; if done, the repair must be carried out by a competent person for repair authorised by Lyon Equipment to make the repair, and in accordance with specified procedures.

These instructions must be strictly adhered to.

Inspection

A thorough inspection should be carried out at least every 6 months by a competent inspector in accordance with these user instructions. A record of these checks should be kept with the product along with these user instructions. In addition, interim inspections should be carried out where products are used intensively, or in particularly harsh environments where damage is more likely to occur, or where legislation or the type of equipment make it necessary.

Pre-use and thorough inspections are essential because the safety of the user

and other people in the vicinity depends on the continuing correct performance of this product.

Bags should be subject to:

- Pre-use checks
- Thorough inspections (at least once every 6 months)
- Interim inspections (as appropriate)

Check that any labels are still intact and readable.

The webbing should be checked by passing it slowly through the hands to detect for damage, e.g. small cuts in the edges, cuts across the face of the webbing, abrasion, softening or hardening of fibres, or ingress of contaminants. Pay particular attention to the inside of any webbing loops.

The whole bag and any accessories should be checked for damage, e.g. cuts, holes, burns, contamination, UV damage, signs of overloading and damage to stitching.

The Maillon Rapide and any connectors supplied should be checked for damage, e.g. signs of wear, corrosion or deformity. Check for correct functioning. If a Maillon Rapide is supplied, following inspection the nut must be correctly and completely screwed onto the bolt with no threads showing.

The plastic drum or liner (if supplied) should be checked for damage, e.g. cracks, splits or deformity. If a lid is supplied check for correct closure.

Zips and/or other closure systems should be checked for correct function, damage and deformation.

Any of these defects may affect the performance of the Bag.

The checks should be undertaken in good light. Any item showing any defect should be withdrawn from service immediately.

It is recommended the Bag is marked with the date of the next or last inspection.

If in any doubt as to the condition of the product, it should be withdrawn from use immediately and not used again unless confirmed by a competent person that it is acceptable to do so.

If the Bag comes into contact with any chemicals, remove it from service and dispose of it so it cannot be used again.

Lifetime, and when to withdraw your equipment from use

Withdraw your equipment from use if any one of the following applies:

- It shows sign of wear and tear / damage that may affect performance
- Markings on the product are no longer legible
- You suspect it may have been exposed to chemical contamination or extreme temperatures
- It fails a periodic inspection
- It has been dynamically loaded or excessively loaded
- It is more than 10 years after the date of manufacture (textile items or items with textile components).
 Metal items have a potentially

indefinite lifespan if stored correctly.
If you have any reason to doubt that it is safe to use.

It is the responsibility of the competent inspector to decide whether the equipment should be put back into use, or permanently withdrawn from use.

Equipment permanently withdrawn from use must be destroyed, and should be recycled where facilities exist.

Certain environmental elements will considerably accelerate wear: salt, sand, dust, snow, ice, moisture, chemicals, sunlight (UV radiation) – list not exhaustive.

Warning: the safe working life of this product may be as short as its first use in extreme circumstances.

If in doubt, do not hesitate to scrap this product.

Inspection records

A record must be kept for each component, subsystem and system, including name and contact details of the manufacturer or supplier, product description, serial number, year of manufacture, date of purchase, date of first use, any other relevant information, and history of periodic examinations and repairs, including dates and details of inspections and repairs, the name and signature of the competent inspector and the next due date for inspection.

An example of a suitable equipment record is shown on this user instruction and can also be downloaded at Iyon.co.uk

Local jurisdiction may dictate that extra information be recorded in the inspection record – check your country's legal requirements. Some products may have features which need special monitoring during periodic inspections, e.g. wear indicators, in which case this information should also be recorded on the inspection record.

Guarantee

In the event of any defect in materials or workmanship please return the product to the dealer, distributor or manufacturer within 3 years of purchase for inspection. We will replace or repair as required. This guarantee does not cover normal wear and tear or accidental damage.

Note to resellers

If the product is re-sold outside the UK and Eire, but within the EU, the reseller is responsible for providing instructions for use, maintenance, periodic examination and for repair in the language of the country in which the product is to be used. The translations must bear the words 'Translation of the original instructions' (in the language of each version) and must be accompanied by the original instructions.

If you require the Intrastat commodity code / customs tariff code or NATO stock number (where applicable) for this product, please contact us via lyon.co.uk

Chemicals

Avoid all contact with chemical reagents that could affect the performance of the Rated Bag e.g. acids, caustic substances and oxidising agents. Discard this product immediately if contamination is even suspected to have occurred.

Materials

The body of the Bag is PVC coated polyamide.

19 mm, 25 mm, 38 mm, 45 mm and 50 mm webbing is polypropylene, 45 mm webbing is polyester.

18 mm webbing is polyamide.

The thread is polyamide.

Maillon Rapide (if fitted) is galvanised steel.

Adjustment buckles are stainless steel. Captive connectors are steel.

Customer's own marking/ serialisation

Marking, if required, can be made by attaching a tag to the Bag. Ensure that any tags do not interfere with the function or performance of the Bag, and cannot be accidentally used as a means of attachment.

Alternatively, the Bag itself may be marked with an indelible laundrymarker, taking care that the ink does not contaminate any load bearing parts (webbing or stitching).

Markings

ĽΥΟΝ	Manufacturer's logo
Ti	Refer to user instructions
idN	Individual serial number will be in the format YYDDD 12345. The first two digits give the year of manufacture, the next three digits the day of the year from 201 to 365 and the five digits after is the number in the series
WLL	Working Load Limit in kg
xx Ltr	Capacity in litres (where xx is the volume) where marked.
L***	Product code

A label on the bag shows the correct configuration for lifting.

End of document

			Lyon Product Inspection Record	cord		
Product code		Product description	Year of manufacture		Purchase date	
Length if applicable		Individual serial number	Date of first use		Certificate of conformity number	
Manufacturer Lyon Equipment Ltd.		Address Unit 3-7 Tebay Business Park Old Tebay Perrith CA 10 3SS	Tel +44 (0) 15396 24040 Fox +44 (0) 15396 26330 info@yon.co.uk iyon.co.uk	5396 24040 5396 26330 JK	Other relevant information	
D			 Record of inspection and repair			
Date	Comments			Name and signature o	Name and signature of competent inspector	Next due date
oade						
ed fro						
om ly						
ron.c						
o.uk						
ΕN		All user instructions suppli∈	All user instructions supplied with this product must be kept as part of the product inspection record	part of the product inspe	ection record	





Lyon Equipment Limited Units 3-7, Tebay Business Park, Old Tebay, Penrith,

Cumbria, United Kingdom, **CA10 3SS**

+44 (0) 15396 24040 Tel: info@lyon.co.uk Email:

Web: lyon.co.uk

Declaration of Conform hese instructions and a For more detailed user



© Lyon Equipment 2019

Notified body controlling manufacture (where applicable)

Where items of Personal Protective Equipment require an EU type examination in accordance with Personal Protective Equipment (EU) Regulation 2016/425, the body controlling the manufacture is: Notified body No. 0598 SGS Fimko Oy, P.O. Box 30 (Särkiniementie 3), 00211 HELSINKI, Finland.

WARNING

Make sure that you have read and understood these instructions before using this equipment. These user instructions are to be read and kept along with any other user information provided.

Activities at height are hazardous and may lead to injury or death. It is the user's responsibility, at all times, to ensure that they understand the correct use of any equipment supplied by or through Lyon Equipment, use it only for the purposes for which it is designed, and practice proper safety procedures including having a rescue plan in case of emergency.

This product must not be used outside its limitations, or for any purpose other than those described in the user instructions. Misuses forbidden in these instructions are examples only; many other misuses may exist which could lead to injury or death.

Do not use combinations of items of equipment in which the safe function of any one item is affected or interferes with the safe function of another.

Please note, the information in these user instructions is not exhaustive, and is not a substitute for comprehensive instruction and training by a competent person.

Lyon Equipment is not responsible for any consequences, whether direct, indirect or accidental, resulting from the use of its products. If you are unsure about the correct use of this product, please contact us.

Who can use this equipment

This equipment should only be used by trained, competent and responsible persons, or the user should be under the direct supervision of a trained, competent and responsible person.

Activities at height should not be undertaken by persons affected by alcohol or drug dependence, diabetes, epilepsy, fits, blackouts, fear of heights, vertigo / dizziness / difficulty with balance, heart disease / chest pain, high or low blood pressure, impaired limb function, obesity, psychiatric illness, musculoskeletal issues, e.g. a bad back.

General instructions for use

Equipment must be checked before each use, to ensure it is serviceable and operates correctly. Checks should also be carried out during use. In addition, a thorough inspection by a competent inspector should be carried out in strict accordance with these user instructions, and a record kept of these inspections.

This product may be used with any compatible item of equipment, keeping in mind the limitations of each item in the safety chain. It should be noted that a full body harness is the only type of harness which may be used in a fall arrest system.

The anchor device or anchor point is of primary importance and should be unquestionably reliable. It should be strong enough to withstand the foreseeable maximum load that could be applied e.g. in the event of a fall.

When selecting an anchor, the anticipated directions of loading and potential loads should be taken into account.

Anchors should be selected and positioned to allow work to be carried out in such a way as to minimise the potential for a fall and potential fall distance, for example by keeping the anchor point / device above the user.

Anchors should not have sharp or rough edges which could damage equipment (use edge protection if necessary).

On each occasion of use, verify the free space required beneath the user in order to avoid an impact. Always try to place protection so that any fall will be stopped before the user hits the ground or any other obstruction. Remember to allow for rope stretch and slippage in the belay device or rope ascender / descender. In a fall arrest situation, the user must be protected from dynamic forces of greater than 6 kN in the event of a fall, e.g. by use of a fall arrest system incorporating an EN 355 energy absorber.

Maintaining your equipment

Wash in clean water not exceeding 30°C with pure soap and rinse in clean cold water: Do not use chemical products, solvents or detergents – these should be regarded as harmful.

Due to the difficulties in effectively disinfecting equipment, we recommend that any contaminated equipment should be withdrawn from use and disposed of in a suitable manner.

Equipment must be clean and dry before storing. Always allow to dry naturally, away from direct heat. Equipment should be stored in a cool, dry, well-ventilated area, away from excessive heat, high humidity, sharp edges, corrosives, sunlight or other sources of ultraviolet light (UV) and other possible causes of damage.

During transport, this product should be protected from abrasion, mechanical damage, chemical contamination, UV and heat.

Textiles

Always keep textile items at temperatures between -30°C and +50°C.

Metal items

Always keep metal items at temperatures between -20°C and +60°C.

No alterations, additions or repairs may be made to this product without the manufacturer's prior written consent; if done, the repair must be carried out by a competent person for repair authorised by Lyon Equipment to make the repair, and in accordance with specified procedures.

These instructions must be strictly adhered to.

Inspection

A thorough inspection should be carried out at least every 6 months by a competent inspector in accordance with these user instructions. A record of these checks should be kept with the product along with these user instructions. In addition, interim inspections should be carried out where products are used intensively, or in particularly harsh environments where damage is more likely to occur, or where legislation or the type of equipment make it necessary.

Pre-use and thorough inspections are essential because the user's level of protection depends on the continuing correct performance of this product.

PPE (Personal Protective Equipment) inspection training is available from Lyon Equipment.

Lifetime, and when to withdraw your equipment from use

Withdraw your equipment from use if any one of the following applies:

- It shows sign of wear and tear / damage that may affect performance
- Markings on the product are no longer legible
- You suspect it may have been exposed to chemical contamination or extreme temperatures
- It fails a periodic examination
- It has been used to arrest a fall or has been excessively loaded
- It is more than 10 years after the date of manufacture (textile items or items with textile components).
 Metal items have a potentially indefinite lifespan if stored correctly.
- If you have any reason to doubt that it is safe to use.

It is the responsibility of the competent inspector to decide whether the equipment should be put back into use, or permanently withdrawn from use. Equipment permanently withdrawn from use must be destroyed, and should be recycled where facilities exist.

Certain environmental elements will considerably accelerate wear: salt, sand, dust, snow, ice, moisture, chemicals, sunlight (UV radiation) – list not exhaustive.

Warning: the safe working life of this product may be as short as its first use in extreme circumstances.

If in doubt, do not hesitate to scrap this product.

Guarantee

In the event of any defect in materials or workmanship please return the product to the dealer, distributor or manufacturer within 3 years of purchase for inspection. We will replace or repair as required. This guarantee does not cover normal wear and tear or accidental damage.

Note to resellers

If the product is re-sold outside the UK and Eire, but within the EU, the reseller is responsible for providing instructions for use, maintenance, periodic examination and for repair in the language of the country in which the product is to be used.

If you require the Intrastat commodity code / customs tariff code or NATO stock number (where applicable) for this product, please contact us via lyon.co.uk

Inspection records

A record must be kept for each component, subsystem and system, including name and contact details of the manufacturer or supplier, product description, serial number, year of manufacture, date of purchase, date of first use, any other relevant information, and history of periodic examinations and repairs, the name and signature of

the competent inspector and the next due date for inspection. An example of a suitable equipment record is shown on this user instruction and can also be downloaded at lyon.co.uk

Local jurisdiction may dictate that extra information be recorded in the inspection record – check your country's legal requirements. Some products may have features which need special monitoring during periodic inspections, e.g. wear indicators, in which case this information should also be recorded on the inspection record.

This page deliberately left blank

Explanation of symbols

Explanation of	-7
[II]	Refer to user instructions
	Permitted use
\triangle	Caution
\$@\$	Danger of death
	Telephone number
土	Anchor point
	Rope diameter
	Cable
SWL 250kg	SWL (Safe Working Load)

			Lyon Product Inspection Record	ord		
Product code		Product description	Year of manufacture		Purchase date	
Length if applicable		Individual serial number	Date of first use		Certificate of conformity number	
Manufacturer Lyon Equipment Ltd		Address Uni 3-7 Teboy Business Park Old Teboy CAL 0 3SS	Tel +44 (0) 15396 24040 Fox. +44 (0) 15396 20330 Inf@@yon.co.uk Iyon.co.uk	396 24040 8396 26330 k	Other relevant information	
D	-		Record of inspection and repair			
Date	Comments			Name and signature o	Name and signature of competent inspector	Next due date
oade						
d fra						
om ly						
ron.c						
o.uk						
EN		All user instructions supplied	All user instructions supplied with this product must be kept as part of the product inspection record	part of the product insp€	ection record	