

# Impact Driver LXT®

## DTD156

18V • 1/4" • 155 Nm • 0 – 2 500 min<sup>-1</sup>

### Compact brushless impact driver for quick driving

A compact and light impact wrench with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 155 Nm, suitable for quick driving. A handy LED light for added lighting.



**LXT**

### Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
No load speed	0 - 2500 min <sup>-1</sup>
Max Fastening Torque Impact Drill	155 Nm
Tightening Capacity Standard Bolt	M5 - M14
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M12
Impacts per Minute (IPM)	0 - 3000 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	103 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	92 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	10,0 m/s <sup>2</sup>
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Tool weight with battery (EPTA)	1,3 - 1,6 kg
Product Dimensions (L x W x H):	143 x 79 x 241 mm

### User benefits

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site
- A high impact torque is achieved with the impact screwdriver.
- The screw tip is securely held in place by a quick lateral stroke
- Quick mount for 1/4 "screwdriver
- The narrow design of the handle ensures excellent handling

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ Other

User manual

Parts drawing