

Combi Drill LXT®

DHP453

18V • 42 Nm • 0 – 1 300 min⁻¹

Combi drill with hammer action for demanding amateur builders

For screwdriving and drilling with or without hammer action, two power settings. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use



LXT

■ Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
No load speed	0 - 400 / 1300 min ⁻¹
Max. fastening torque Hard/Soft	42 / 27 Nm
Torque setting	16
Impacts per Minute (IPM)	0 - 6000 / 19500 min ⁻¹
Max. Drilling Diameter in Wood	36 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Steel	13 mm
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	94 dB(A)
Sound Pressure Level (L _{pA})	83 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Vibration Level (3 axes), Impact Drilling	10,0 m/s ²

■ User benefits

- The rubber coating on the handle ensures a firm working grip
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - www.makita.com



Related products

Optional AC

158777-2

Plastic carrying case



196306-3

Keyless chuck 13 mm, 1/2" - 20UNF



450128-8

Battery cover, LXT®, 14,4 – 18V



BL1820B

Battery LXT® 2,0 Ah



BL1830B

Battery LXT® 3,0 Ah



BL1840B

Battery LXT® 4,0 Ah



BL1850B

Battery LXT® 5,0 Ah



BL1860B

Battery LXT® 6,0 Ah



D-42204

COUNTERSINK 6PC SET



D-47139

Holesaw Set



D-47363

Forstner Drill Bit Set, 5 pcs



E-08698

Flat bit set 8 pcs



Other

[User manual](#)

[Parts drawing](#)