

## Combi Drill LXT®

# DHP482

18V • 62 Nm • 0 – 1 900 min<sup>-1</sup>

**Powerful general-use combi drill with hammer action for professionals**

An efficient drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 62 / 36 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.



### ■ Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
No load speed	0 - 600 / 1900 min <sup>-1</sup>
Max. fastening torque Hard/Soft	62 / 36 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 9000 / 28500 min <sup>-1</sup>
Max. Drilling Diameter in Wood	38 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Concrete	13 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L <sub>WA</sub> )	93 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	82 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ **Optional AC**

### **BL1820B**

Battery LXT® 2,0 Ah

### **BL1840B**

Battery LXT® 4,0 Ah

### **BL1860B**

Battery LXT® 6,0 Ah

### **BL1830B**

Battery LXT® 3,0 Ah

### **BL1850B**

Battery LXT® 5,0 Ah

---

## ■ **Other**

**User manual**

**Parts drawing**