8174 Rope Grab Family - USA

Description

Lightweight, manual rope grabs move easily up and down vertical lifelines to provide continuous fall protection. In the event of a fall, Miller rope grabs lock quickly.

Materials_

Rope Grabs: Stainless Steel

Attachments

Rope Lanyard: 5/8" (16mm) Synthetic Rope

Web Lanyard: Polyester

Snap Hook: Clear Zinc Chromate Plated

Forged Alloy Steel

Proof tested to 3,600lbs (16kN)

Technical.

Min. Tensile Strength

Rope Grab:
3,600lbs (16kN)

Snap Hook:
5,000lbs (22.2kN)

SofStop:
5,000lbs (22.2kN)

Manyard:
5,000lbs (22.2kN)

Max Working Load:
310lbs (141kg)

Weights:
see chart

One of the property of

O-Ring Inner Diameter: 2.145" (54.4mm)

Certification_

Meets OSHA 1910.66, 1926.502, ANSI A10.32, Z359.1 requirements.

Model #	Weight	Description
8174/U		Stainless steel, manual rope grab for use with 5/8" (16mm) or 3/4" (19mm) synthetic rope
8174MLS4/FTYL	. 5/	8174/U w/ attached 4ft (1.2m) Manyard shock absorbing lanyard with locking snap hook
8174RLS/2FTWH	, ,	
		8174/U w/ attached 2ft (0.6m) rope lanyard with locking snap hook
8174WLS/2FTYL	2.94lb (1.33kg)	8174/U w/ attached 2ft (0.6m) web lanyard with locking snap hook
98174LS/3FTYL	2.25lb (1.02kg)	8174/U w/ attached 3ft (0.9m) lanyard & SofStop shock-absorber with locking snap hook



Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.

