



In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
PPE inspection should be conducted with the manufacturer's Instructions for Use.
Download the instructions at PETZL.COM.





## EACYTOD / EACYTOD WALL

| User information  | STIOP WALL      | ■<br>PPE informa | tion                         |           |            |     |              |     |
|---|-----------------|------------------|------------------------------|-----------|------------|-----|--------------|-----|
| Surname   |                 | Model            |                              |           |            |     |              |     |
| Address   |                 | Serial number    |                              |           |            |     |              |     |
|   |                 | Year of manufa   | acture                       |           |            |     |              |     |
|   |                 | Date of purcha   | ase                          |           |            |     |              |     |
| Identifier  |                 | Date of first us |                              |           |            |     |              |     |
| isonans.  |                 |                  | r: Petzl, Zl Cidex 105A - 38 | 920 Croll | es - Franc | ne. |              |     |
|   |                 | Manadatare       | 11 (izi, zi Gidox 100/1 (ici | 020 0101  | oo mana    | ,0  |              |     |
| Ø   | Q               | ×                | <b>⊗</b> ▶ 📆                 |           |            |     | N/A          |     |
| Good condition (G)  | To monitor (TM) | To repair (TR)   | Do not use, retire (F        | R)        |            | Not | applicable   |     |
| Known product history Usage conditions or exceptional event du fall or fall arrest, use or storage at extreme modification outside manufacturer's facilit   | e temperatures, |                  |                              |           |            |     |              |     |
|   |                 |                  |                              | <b>⊘</b>  | Q          | X   | <b>⊗</b> ▶ 📆 | N/A |
| 2. Preliminary observations  • Verify the presence and legibility of the serial number and the CE mark.  • Verify that the product lifetime has not been exceeded.  • Compare with a new device to verify there are no modifications or missing elements.   |                 |                  |                              | 0         |            | 0   | 0            | 0   |
| <ul> <li>3. Inspecting the frame</li> <li>Check the condition of the frame (marks, cracks, wear, deformation, corrosion).</li> <li>Check for wear caused by rope running through the device. Use the included inspection pin or a 4mm diameter bar.</li> <li>Check the condition of the anchor attachment hole (marks, cracks, wear, deformation, corrosion).</li> </ul>  |                 |                  |                              | 0         |            | 0   | 0            |     |
| 4. Inspecting the primary gate  • Check the condition of the gate (marks, cracks, wear, deformation, corrosion).  • Manually verify that the gate opens completely.  • Verify that the gate closes automatically and that the return spring works.  • Check the condition of the rivet (cracking, deformation, corrosion).  |                 |                  |                              | 0         |            |     | 0            | 0   |
| <ul> <li>5. Checking the auto-locking gate</li> <li>Check the condition of the gate (marks, cracks, wear, deformation, corrosion).</li> <li>Manually verify that the gate opens completely.</li> <li>Verify that the gate closes automatically and that the return spring works.</li> <li>Check the condition of the rivet (cracking, deformation, corrosion).</li> </ul> |                 |                  |                              | 0         | 0          | 0   | 0            | 0   |
| 6. Checking the EASYTOP WALL anchor  • Check the condition of the anchor (marks, cracks, wear, deformation, corrosion).  • Check the condition of the structure mounting holes (marks, cracks, wear, deformation, corrosion).  • Check the condition of the EASYTOP installation bolt (marks, cracks, wear, deformation, corrosion).                                      |                 |                  |                              | 0         | 0          | 0   | 0            | 0   |
|   |                 |                  |                              |           | _          |     |              |     |
| Comments (detail here any defects found on the product and accomplished tasks)  |                 |                  |                              |           |            |     |              |     |
|   |                 |                  |                              |           |            |     |              |     |
| VERDICT   |                 | Inspected by     |                              |           |            |     |              |     |

Company

Date

Product fit to remain in service

Product **unfit** to remain in service

Next inspection date