

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at PETZL.COM.



TWIN RELEASE

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

<input checked="" type="radio"/> Good condition (G)	<input type="radio"/> To monitor (TM)	<input type="radio"/> To repair (TR)	<input type="radio"/> Do not use, retire (R)	<input type="radio"/> N/A Not applicable
---	---------------------------------------	--------------------------------------	--	---

1. Known product history
 Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
----------------------------------	-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

3. Checking the moving side plates

- Check the condition of the moving side plates (wear, marks, deformation, cracks, corrosion, dirt...).
- Verify that the side plates rotate properly.
- Check the condition of the external brake (wear, cracks, marks, deformation, corrosion, dirt...).
- Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play...).

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

4. Checking the attachment holes

- Check the condition of the swivel (wear, marks, deformation, cracks, corrosion, dirt...).
- Check that the swivel rotates in both directions.
- Check the condition of the auxiliary attachment hole (wear, marks, deformation, cracks, corrosion, dirt...).

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

5. Checking the sheaves

- Check the condition of the sheaves (wear, marks, deformation, cracks, corrosion, dirt...).
- Verify that the faceted sheave turns in the desired direction and blocks in the other direction.
- Count the number of clicks of the ratcheting wheel. You must hear 12 clicks during one complete rotation.
- Verify that the sheave turns freely in both directions.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

6. Checking the handle

- Check the condition of the handle (wear, marks, deformation, cracks, corrosion, dirt...).
- Check that the handle return spring is working properly.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

7. Inspecting the cam

- Check the condition of the cam (wear, marks, deformation, cracks, corrosion, dirt...).
- Check that the cam return spring is working properly.
- Verify that the cam blocking button is working properly.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

8. Checking the side plates' opening and locking systems

- Check the condition and function of the locking system on each side plate (marks, deformation, dirt, effectiveness of the return spring(s)).

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

9. Function check

- Set up a 4:1 system with a compatible rope and double pulley in accordance with the TWIN RELEASE SYSTEM Instructions for Use. Install the system on an anchor at low height and suspend a mass on the rope. Check for proper rope travel when hauling, proper blocking function, the ability to lower the mass by operating the handle.

<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
-----------------------	-----------------------	-----------------------	-----------------------	-----------------------

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date Next inspection date