

A high-performance workhorse designed for the professional rope access technician. Ideal for use with bollard-type descent devices like the PMI D4, this 100% nylon static rope has a 40 carrier sheath with an excellent hand, as well as great knotability and abrasion resistance.

**Key Features:**

Ultra-smooth sheath design • Optimized for Rope Access • Works well with a variety of devices • Excels in abrasive environments

*Material: Nylon Sheath/Nylon Core*

**11 mm (7/16")**

*Weight: 85 g/m*

*MBS: 33.3 kN (7476 lbf)*

*Elongation at 10% MBS: 5.2%*

*Elongation: 1.4% at 300 lbf | 3.4% at 600 lbf | 6.0% at 1000 lbf | 9.1% at 1800 lbf*

**Blue**

1 m (3.3 ft)


KR110BL001ES

100 m (328 ft)

KR110BL100ES

200 m (656 ft)

KR110BL200ES



**Red**

1 m (3.3 ft)


KR110RD100ES

100 m (328 ft)

KR110RD100ES

200 m (656 ft)

KR110RD200ES



**Yellow**

1 m (3.3 ft)


KR110YL001ES

100 m (328 ft)

KR110YL100ES

200 m (656 ft)

KR110YL200ES



**CERTIFIED** NFPA 1983 (2017), T CI1801, Static EN 1891-A

A large, empty rectangular box with a thin black border, intended for handwritten notes.