

PMI® Classic static rope has been at the heart of mountaineering and caving worldwide for over 30 years. Extreme durability and substance you can rely on are what this rope is known for. Built to exacting Cordage Institute Life Safety Rope requirements, this rope features a hard-wearing 16-carrier nylon sheath and a static core design. PMI® Classic Sport rope normally features an EZ-Bend Sheath, offering a fine balance between extraordinary abrasion-resistance and good knotability.

For even greater abrasion resistance, consider asking about PMI® MaxWear. Characterized by greater sheath tension, the knotability of PMI® Classic MaxWear isn't anything to write home about, but for durability it simply can't be beat. Any of the ropes below can be ordered with the MaxWear sheath design - just replace the E at the end of the part number with an M . . . Or ask your friendly PMI representative to assist you.

Key Features:

16 carrier construction • Nylon • Classic construction

9 mm (23/64")

Weight: 53 g/m

MBS: 18.3 kN (4114 lbf)

Elongation: 3.7% at 300 lbf | 5.4% at 600 lbf | 7.6% at 1000 lbf

Elongation at 10% MBS: 4.3%



COMPLIANT

CI1801, Static

46 m (150 ft) SR090WZ046E

61 m (200 ft) SR090WZ061E

92 m (300 ft) SR090WZ092E

183 m (600 ft) SR090WZ183E

200 m (656 ft) SR090WZ200E

10 mm (25/64")

Weight: 66 g/m

MBS: 30.1 kN (6769 lbf)

Elongation: 1.9% at 300 lbf | 4.0% at 600 lbf | 6.4% at 1000 lbf

Elongation at 10% MBS: 4.5%



COMPLIANT

CI1801, Static

46 m (150 ft) SR100WZ046E

61 m (200 ft) SR100WZ061E

92 m (300 ft) SR100WZ092E

183 m (600 ft) SR100WZ183E

200 m (656 ft) SR100WZ200E

11 mm (7/16")

Weight: 80 g/m

MBS: 32.7 kN (7344 lbf)

Elongation: 1.6% at 300 lbf | 3.0% at 600 lbf | 5.8% at 1000 lbf

Elongation at 10% MBS: 3.9%



COMPLIANT

CI1801, Static

46 m (150 ft) SR110WZ046E

61 m (200 ft) SR110WZ061E

92 m (300 ft) SR110WZ092E

183 m (600 ft) SR110WZ183E

200 m (656 ft) SR110WZ200E

12.5 mm (1/2")

Weight: 104 g/m

MBS: 42 kN (9442 lbf)

Elongation: 1.3% at 300 lbf | 2.9% at 600 lbf | 4.7% at 1000 lbf

Elongation at 10% MBS: 4.2%



COMPLIANT

CI1801, Static

46 m (150 ft) SR125WZ046E

61 m (200 ft) SR125WZ061E

92 m (300 ft) SR125WZ092E

183 m (600 ft) SR125WZ183E

200 m (656 ft) SR125WZ200E



A large, empty rectangular box with a thin black border, intended for handwritten notes or a signature.