

FP01 - Temporary Horizontal Lifeline

Collection: Anchorage Device

Range: Fall Protection

Materials: Polyester, Alloy Steel, Heat Treated

Outer Carton: 4

Product information

Constructed with precision engineering and rigorously tested to meet industry standards, the temporary horizontal lifeline is quick and easy to install, extending up to 20 metres in length. Once elevated, this lifeline allows up to two workers to move safely along the line.

Anchorage Device

Anchorage devices are common fall protection solutions in work areas that lack existing anchor points for personnel tie-off. They are certified to the EN 795 standard, making them approved anchor points for any elevated work area that poses a risk of fall to the worker. These points are responsible for connecting the user to a lifeline or lanyard making them must-haves for the safety of workers at height.

Fall Protection

Fall Protection is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of fall protection products for working at height.

Standards

EN 795 NONE



Features

- CE-CAT III
- Quick and easy installation
- Ratchet tensioner for quick and easy adjustments
- Attached Bag for Easy Transport and Storage
- No additional tools required
- Can be used by two workers at the same time

FP01 - Temporary Horizontal Lifeline

Commodity Code: 5609000000

Test House

Cert No: CE_C_0506_19_68_01_4A

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m ³)	EAN13	DUN14
FP01YBR	Yellow/Black	55.0	35.0	20.0	3.3550	0.0385	5036108279845	15036108769886