

PRODUCT SPECIFICATION & TECHNICAL DATA

PS44 - Top Ear Muff

Collection: Ear Muffs **Range:** Hearing Protection **Materials:** ABS, Foam

Product information

Lightweight and foldable ear muff, with a padded headband for added comfort. Great attenuation level, ideal to protect against harmful noise in the work environment.

Standards

EN 352-1 NONE (SNR 33dB)

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Features

- Adjustable length for a secure and comfortable fit
- Lightweight and comfortable
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- Folds to palm size for better carriage and to keep clean
- Padded headband for comfort
- CE-CAT III
- Certified





PRODUCT SPECIFICATION & TECHNICAL DATA

PS44 - Top Ear Muff Commodity Code: 6506101000

Test House Cert No: PPE18161238

CARTON DIMENSIONS/WEIGHT

| Item | Colour | Len | Wid | Hgt | Weight (Kg) | Cubic (m ³) | EAN13 | DUN14 |
|---------|--------|------|------|------|-------------|-------------------------|---------------|----------------|
| PS44BKR | Black | 56.0 | 45.0 | 58.0 | 0.3500 | 0.1462 | 5036108296866 | 15036108786609 |

PERFORMANCES - SOUND ATTENUATION - EN352-1:2002

| PS44 | | | | | | | | | | |
|---|------|------|------|------|------|------|------|--|--|--|
| A Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | | | |
| B Means Attenuation (dB) | 22.8 | 24.4 | 31.6 | 41.7 | 37.3 | 39.4 | 35.9 | | | |
| C Standard Deviation (dB) | 3.2 | 3.5 | 3.4 | 3.4 | 3.5 | 3.7 | 4.4 | | | |
| D Assumed Protection (dB) | 19.6 | 20.9 | 28.2 | 38.3 | 33.8 | 35.7 | 31.5 | | | |
| SNR = 33 dB H = 34 dB / M = 31 dB / L = 24 dB | | | | | | | | | | |

PS44BKR