

PRODUCT SPECIFICATION & TECHNICAL DATA

PS46 - Premium Ear Muff

Collection: Ear Muffs Range: Hearing Protection Materials: ABS, PU Foam, PVC

Product information

Premium Ear Muff with PU padded headband that provides maximum comfort during long periods of use. Contemporary styling with dual pin adjustable cups for an optimised fit. Excellent attenuation performance provides superior protection against harmful noise.

Standards

EN 352-1 NONE (SNR 34dB)

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Features

- New style
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- Light and robust
- Adjustable dual pin system provides multiple positioning for better fit
- Padded headband for comfort
- CE-CAT III
- SNR 34dB attenuation level
- Certified





PRODUCT SPECIFICATION & TECHNICAL DATA

PS46 - Premium Ear Muff Commodity Code: 6506101000

Test House

Cert No: 2777_10668_01_E00_00

CARTON DIMENSIONS/WEIGHT

| Item | Colour | Len | Wid | Hgt | Weight (Kg) | Cubic (m ³) | EAN13 | DUN14 |
|---------|--------|------|------|------|-------------|-------------------------|---------------|----------------|
| PS46GRR | Grey | 64.0 | 39.0 | 50.0 | 0.3000 | 0.1248 | 5036108296446 | 15036108786210 |

PERFORMANCES - SOUND ATTENUATION

| PS46 | | | | | | | | | | |
|------|---------------------------------|------|------|------|------|------|------|------|--|--|
| А | Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | | |
| В | Mean Attenuation (dB) | 20.5 | 23.0 | 33.5 | 41.8 | 37.8 | 39.7 | 38.3 | | |
| C | Standard Deviation (dB) | 2.7 | 2.3 | 1.9 | 2.4 | 2.8 | 3.2 | 3.0 | | |
| D | Assumed Protection (dB) | 17.8 | 20.7 | 31.6 | 39.4 | 35.1 | 36.5 | 35.3 | | |
| SN | SNR 34dB H:36dB M: 32dB L: 24dB | | | | | | | | | |

PS46GRR