

### PW43 - Comfort Ear Protector

**Collection:** Ear Muffs

**Range:** Hearing Protection

**Materials:** ABS, PVC, PU Foam

**Inner Pack:** 10

**Outer Carton:** 40

#### Product information

This ear protector is constructed to be both durable and ultralightweight. It has broad foam cushions, high impact ABS cups (filled with sound absorbing foam) and comfort headband.

#### Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

#### Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

#### Standards

ANSI S3.19 NONE (NRR 26dB)

EN 352-1 NONE (SNR 32dB)



#### Features

- Padded headband for comfort
- Light and robust
- Adjustable length for a secure and comfortable fit
- Certified
- CE-CAT III
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines

**PW43 - Comfort Ear Protector**  
**Commodity Code: 6506101000**

**Test House**

Cert No: Q1264A

Cert No: PPE 18161204

**CARTON DIMENSIONS/WEIGHT**

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m <sup>3</sup> )	EAN13	DUN14
PW43BKR	Black	65.0	43.0	55.0	0.2400	0.1537	5036108161430	15036108690548

**PERFORMANCES - SOUND ATTENUATION - EN352-1:2002**

<b>PW43</b>								
A	Frequency (Hz)	125	250	500	1000	2000	4000	8000
B	Means Attenuation (dB)	19.1	22.4	30.1	38.9	33.4	39.6	37.6
C	Standard Deviation (dB)	2.2	2.5	2.0	2.3	2.2	2.1	2.6
D	Assumed Protection (dB)	16.9	19.9	28.1	36.6	31.2	37.5	35.0
SNR = 32dB H = 34 dB / M = 30 dB / L = 23 dB								

**PERFORMANCES - SOUND ATTENUATION - ANSI S3 19-1974** *Tested by Michael & Associates, Inc.*

<b>PW43</b>										
A	Frequency(Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Mean Attenuation (dB)	17.8	21.8	29.1	38.4	36.3	40.6	40.6	37.1	39.0
C	Standard Deviation (dB)	2.8	2.3	1.8	2.7	2.7	3.1	3.2	3.8	2.8
NNR (NOISE REDUCTION RATING) = 32dB										

PW43BKR