

PRODUCT SPECIFICATION & TECHNICAL DATA

PW65 - BizWeld Plus Welding Helmet

Collection: Head Protection

Range: PPE

Materials: Polyethylene, PP, Nylon

Product information

Auto-darkening welding helmet, which switches from a light to dark state when welding activity starts. Light state is DIN 4; Dark state is adjustable from DIN 9 to DIN 13 using the external knob. Response time from light to dark state is 0.04 milliseconds; return from dark to clear state in 0.03-0.04 sec. Power is supplied by solar cells with 2 built-in lithium batteries to offer power back-up for longer service life. No need for replacement batteries.

Standards

EN 166 NONE (1 S) EN 175 NONE (F) EN 379 NONE (4 / 9-13; 1/1/1/2) CE NONE

Head Protection

PW rapidly expanding head protection product range aims to benefit our customers by combining the most updated styles and standards in head protection, irrespective of job or location. A wide selection of compatible accessories is also available. A full explanation of features and performances are given in order to help you make a more informed choice.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Features

- Certified
- Retail box which aids presentation for retail sales
- · Wheel ratchet size adjustment for easy fitting
- Suitable for a wide range of applications
- Suitable to be worn with disposable respirators
- Solar cell power with two built-in lithium back-up batteries and a working time of over 5000 hours
- Auto-darkening, switches from light to dark when the welding process starts
- Superior optical quality LCD filter





PRODUCT SPECIFICATION & TECHNICAL DATA

PW65 - BizWeld Plus Welding Helmet Commodity Code: 9004901000

Test House

Cert No: C5466PW_R1

Cert No: C5467PW_R1

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
PW65BKR	Black	65.0	45.0	39.0	0.8800	0.1141	5036108255566	15036108744470