

Data sheet

PEANUT Y



GENERAL

| | | | |
|-----------|--|-----------------|-------------|
| Art. no.: | HSG-022-2,5-5 | E-class number: | 40-02-01-03 |
| EAN: | 4030281183464 | Customs no.: | 84798997 |
| Standard: | BASED ON EN 354:2010 EN 360:2002 RFU CNB/P/11.060 RFU CNB/P/11.085 | | |

Data sheet

PEANUT Y

The compact connecting device PEANUT Y with FS92 karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the fall height is extremely low. The karabiner with an opening width of 90 mm is particularly suitable for large structures such as high shelves or lattice mast structures. The lanyard is perfectly suited for continuous, reciprocal securing - even at lower heights. The PEANUT Y is edge-suitable and therefore also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 2.5 m long arms, the PEANUT Y is ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Fall indicator

| | |
|-------------------------|------------------------|
| Suitable for edges: | yes |
| Max. service life: | 10 Years |
| Max. number of persons: | 1 |
| Rated load: | 135 KG |
| Patent | |
| Temperature: | from 45 °C to -35 °C |
| Suspension element: | BAND |
| Area of application: | High Rack, Scaffolding |

DIMENSIONS

| | |
|---------|---------|
| Size: | 2,5m |
| Weight: | 3,63 kg |

HARDWARE

Carabiner on anchoring point side:

FS 92

Carabiner on belt side: STAK TRI

MATERIAL

Material:

Polyester, Polyamide, Steel
