

Data sheet

MARK 1 PLUS



GENERAL

Art. no.:	A-031
EAN:	4030281180289
Standard:	DIN EN 12841-C:2006 DIN EN 341-2A:2011

E-class number:	40-02-01-06
Customs no.:	76169990

Data sheet

MARK 1 PLUS

The abseil device Mark 1 Plus is the only repelling device meeting EN 341-2A:2011 and EN 12841-C:2006.

Usage according to EN 341-2A:

In combination with the Skylotec Super Static 11 mm-rope, Mark 1 Plus can be used with weights 30 - 160kg and a max. abseil height of 190m.

Usage according to EN 12841-C:

In combination with ropes meeting EN 1891-A , Mark 1 Plus can be used with ropes between 9 - 12mm.

Max. weight load:

9mm = 130kg

10-12mm = 200kg

with panic feature

FEATURES

Abseiling speed:	2,00 m/s
------------------	----------

Max. service life:	30 Years
--------------------	----------

Max. number of persons:	1
-------------------------	---

Temperature:	from 60 °C to -35 °C
--------------	----------------------

Area of application:	
----------------------	--

Fire brigade / Rescue / Special Forces, Rope Access / Rigging

DIMENSIONS

Size:	205 x 34 x 85mm
-------	-----------------

Weight:	0,43 kg
---------	---------

MATERIAL

Material:	Aluminium
-----------	-----------