

Data sheet

IGNITE ION





GENERAL

G-1130-M/XXL
4030281222255
EN 361:2002

E-class number:	40-02-01-02
Customs no.:	63079098



Data sheet

IGNITE ION

Our new all-round safety harness for all classical applications in construction and maintenance has above all one major feature due to simplified adjustment options in the chest and leg area as well as three different sizes: exceptional fit!

Even for users who rarely wear personal protective equipment against falls from height, the IGNITE ION is extremely easy to use and self-explanatory. The buckle by Fidlock in the chest area snaps magnetically and closes almost automatically. The two orange roping-up loops made of fabric are approved for joint use and equipped with abrasion indicator for maximum safety.

User-friendly, self-explanatory, safe:

- easy to put on and adjust
- very good fit
- large roping-up loops (chest) with wear indicator

FEATURES

Fal				
⊢ ∩ I	ıın	α	へつせ	\sim r

Shoulder or leg padding:	yes	
Belt strap coiler:	yes	
Hand-washing:	40 °C	
Click buckles:	yes	
Max. service life:	10 Years	
Max. number of persons:	1	
Rated load:	140 KG	
Attachment Points:		
dorsal attachment point, sternal attachment point		
Patent		
Temperature:	from 45 °C to -35 °C	
Area of application:		

Construction / Roofer / Carpenter, Facade / Window Cleaning, High Rack, Lift Construction, Metal Construction, Power Supplies / - Transmission / Telecommunications, Scaffolding

[VIDEO](http://www.skylotec.com/media/content/images/PDF/IGNITE SERIES.mp4)



DIMENSIONS

Size:	M/XXL
Waist size:	80-110cm
Weight:	1,26 kg

MATERIAL

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Polyester

Dorsal attachment point material:

Aluminium

Material Click buckle: Stainless Steel