

Data sheet

IGNITE TRION



GENERAL

Art. no.: G-1131-M/XXL

EAN: 4030281222286

Standard: EN 358:1999
EN 361:2002

E-class number: 40-02-01-02

Customs no.: 63079098

Data sheet

IGNITE TRION

The new high-performance full body harness for industry and trade is uncomplicated and very easy to buckle on. The harness scores with extremely flexible adjustments of belt straps that are passed through the thin but effective hip padding. Due to its asymmetric shape, the padding ensures that the buckle does not exert any pressure in the abdominal area. Ergonomic eyelets are perfectly folded in at the hip without interfering. They are unfolded for use and maintain their position after snapping - if necessary throughout the day. The innovative OKTALOCK click buckles made of stainless steel include new adjustment elements that eliminate undesirable loosening of the belt strap during movement and obviate the need for readjusting during work.

Functionality and ergonomics in abundance:

- asymmetric padding with integrated belt guide
- 4 buckles allow individual adjustments
- retaining eyelets fit the hip ergonomically

FEATURES

Fall indicator

Shoulder or leg padding: yes

Belt strap coiler: yes

Hand-washing: 40 °C

Click buckles: yes

Lanyard Parking-Rings: yes

Max. service life: 10 Years

Max. number of persons: 1

Rated load: 140 KG

Attachment Points:

dorsal attachment point, sternal attachment point,
pole strap attachment point

Patent

Back support: yes

Temperature: from 45 °C to -35 °C

Area of application:

Construction / Roofer / Carpenter, Facade /
Window Cleaning, High Rack, Metal Construction,
Power Supplies / -Transmission /
Telecommunications, Scaffolding, Wind Energy /
Offshore Industry

DIMENSIONS

Size:	M/XXL
Waist size:	80-130cm
Weight:	2,22 kg

MATERIAL

Material:	Polyester, Aluminium, Steel
Webbing material:	Polyester
Sternal attachment point material:	Aluminium
Pole strap attachment point material:	Aluminium
Dorsal attachment point material:	Aluminium
Material Click buckle:	Stainless Steel