

Data sheet

IGNITE ION STRAP





GENERAL

| Art. no.: | G-1135-XS/M |
|-----------|---------------|
| EAN: | 4030281241249 |
| Standard: | EN 361:2002 |
| | |

| E-class number: | 40-02-01-02 |
|-----------------|-------------|
| Customs no.: | 63079098 |
| | |



Data sheet

IGNITE ION STRAP

Our new all-round safety harness for all classical applications in construction and maintenance has above all one major feature due to simplified adjustment options in the chest and leg area as well as three different sizes: exceptional fit!

Even for users who rarely wear personal protective equipment against falls from height, the IGNITE ION is extremely easy to use and self-explanatory. The two orange roping-up loops made of fabric are approved for joint use and equipped with abrasion indicator for maximum safety.

User-friendly, self-explanatory, safe:

- easy to put on and adjust
- very good fit
- large roping-up loops (chest) with wear indicator

FEATURES

| Fal | | |
|-----|--|--|
| | | |
| | | |
| | | |

| Shoulder or leg padding: | yes | |
|---|----------------------|--|
| Belt strap coiler: | yes | |
| Hand-washing: | 40 °C | |
| Click buckles: | yes | |
| Max. service life: | 10 Years | |
| Max. number of persons: | 1 | |
| Rated load: | 140 KG | |
| Attachment Points: | | |
| dorsal attachment point, sternal attachment point | | |
| Temperature: | from 45 °C to -35 °C | |
| Area of application: | · | |

Area of application:

Construction / Roofer / Carpenter, Facade / Window Cleaning, Metal Construction, Scaffolding



DIMENSIONS

| Size: | XS/M |
|-------------|----------|
| Waist size: | 70-100cm |
| Weight: | 1,41 kg |

MATERIAL

Material:

Polyester, Aluminium, Steel

Webbing material: Polyester

Sternal attachment point material:

Polyester

Dorsal attachment point material:

Aluminium

Material Click buckle: Stainless Steel