

Data sheet

DOUBLE TRI



GENERAL

Art. no.:	H-173-TRI-03	E-class number:	40-02-01-05	
EAN:	4030281286288	Customs no.:	76169990	
Standard:	EN 12275-H:2013 EN 362-B:2008			



Data sheet

DOUBLE TRI

With the patented carabiner series DOUBLE, SKYLOTEC provides a solution for all those who work and climb left-handed or use both hands. With the innovative design (180° spring rotation), the sleeve that closes the gate can rotate easily in both directions. Conventional Twist / TriLock carabiners can be turned only to the right; therefore, they are more difficult to use left-handed.

- innovative 180° technology
- for all those who work and climb left-handed or use both hands
- meets both mountaineering and industry standards

GENERAL

Internet only:

Internat. standard: UIAA 121

FEATURES

Breaking load, major axis:

24,00 kN

Breaking load, minor axis:

7,00 kN

Breaking load, open: 8,00 kN

Max. opening: 26 mm

Max. service life: 30 Years

Max. number of persons: 1

Area of application:

Fire brigade / Rescue / Special Forces

DIMENSIONS

 Size:
 112 x 76mm

 Weight:
 0,10 kg



_	Α	\Box	ח	Λ/	Λ	D	
	М	\Box	יע	٧V	М	\Box	

Locking system: Tri

MATERIAL

Material: Aluminium