

Data sheet

DOUBLE-O TRI



GENERAL

Art. no.:	H-176-TRI-03
EAN:	4030281286349
Standard:	EN 12275-H:2013 EN 362-B:2008

E-class number:	40-02-01-05
Customs no.:	76169990

Data sheet

DOUBLE-O TRI

With the patented carabiner series DOUBLE, SKYLOTEC provides a solution for all those who work and climb left-handed or use both hands. With the innovative design (180° spring rotation), the sleeve that closes the gate can rotate easily in both directions. Conventional Twist / TriLock carabiners can be turned only to the right; therefore, they are more difficult to use left-handed.

- innovative 180° technology
- for all those who work and climb left-handed or use both hands
- meets both mountaineering and industry standards

GENERAL

Internet only:

Internat. standard:	UIAA 121
---------------------	----------

FEATURES

Breaking load, major axis:

24,00 kN

Breaking load, minor axis:

7,00 kN

Breaking load, open:	8,00 kN
----------------------	---------

Max. opening:	21 mm
---------------	-------

Max. service life:	30 Years
--------------------	----------

Max. number of persons:	1
-------------------------	---

Area of application:

Arborists, Fire brigade / Rescue / Special Forces,
Rope Access / Rigging, Wind Energy / Offshore
Industry

DIMENSIONS

Size:	109 x 58mm
-------	------------

Weight:	0,09 kg
---------	---------

HARDWARE

Locking system: Tri

MATERIAL

Material: Aluminium
