

Data sheet

DOUBLE-O TWIST



GENERAL

| Art. no.: | H-176-TW | E-class number: | 40-02-01-05 |
|-----------|----------------------------------|-----------------|-------------|
| EAN: | 4030281286592 | Customs no.: | 76169990 |
| Standard: | EN 12275-H:2013 EN 362-B:2008 | | |



Data sheet

DOUBLE-O TWIST

DOUBLE TWIST-O, the new generation of oval carabiner with 180 ° technology and smooth dual-locking mechanism for even more convenience and operational freedom. With the new carabiner series DOUBLE, SKYOLTEC has now an answer for all those who work and climb left-handed or use both hands. With the innovative design (180° spring rotation), the sleeve that closes the gate can rotate in both directions. Conventional Twist/TriLock carabiners can be turned only to the right; therefore, they are more difficult to use for left-handers. Can be used in accordance with mountaineering and industry standard.

GENERAL

Internat. standard: UIAA 121

FEATURES

| Breaking load, major axis: | | | |
|----------------------------|----------|--|--|
| 24,00 kN | | | |
| Breaking load, minor axis: | | | |
| 7,00 kN | | | |
| Breaking load, open: | 8,00 kN | | |
| Max. opening: | 21 mm | | |
| Max. service life: | 30 Years | | |
| | | | |

[VIDEO](http://www.skylotec.com/media/content/images/PDF/DOUBLE.mov)

| Size: | 109 x 58mm |
|-----------------|------------|
| Weight: | 0,09 kg |
| HARDWARE | |
| Locking system: | Twist |
| MATERIAL | |
| Material: | Aluminium |