

Data sheet

PEANUT I



GENERAL

Art. no.:	HSG-021-1,8-1	E-class number:	40-02-01-03
EAN:	4030281181897	Customs no.:	84798997
Standard:	DIN 19427:2017 EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2018		



Data sheet

The compact connecting device PEANUT I with FS90 ALU karabiner convinces with its selfretracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The all-rounder carabiner with an opening width of 60 mm is suitable for almost all structures and can be opened easily. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Fall indicator		
Suitable for edges:	yes	
Max. service life:	10 Years	
Max. number of persons: 1		
Rated load:	135 KG	
Patent		
Temperature:	from 45 °C to -35 °C	
Suspension element:	BAND	
Area of application:		
Facade / Window Cleaning, Fire brigade / Rescue / Special Forces, Mobile Work Platforms		

DIMENSIONS

Size:	1,8m
Weight:	1,67 kg



HARDWARE

Carabiner on anchoring point side: FS 90 ALU Carabiner on belt side: STAK TRI

MATERIAL

Material: Polyester, Polyamide, Aluminium