

Data sheet

PEANUT I



GENERAL

Art. no.:	HSG-021-1,8-5	E-class number:	40-02-01-03
EAN:	4030281181941	Customs no.:	84798997
Standard:	DIN 19427:2017 EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2018		

Data sheet

PEANUT I

The compact connecting device PEANUT I with FS90 ANSI karabiners convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The steel karabiner with 50 kN is particularly robust due to its reinforced gate. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Fall indicator

Suitable for edges: yes

Max. service life: 10 Years

Max. number of persons: 1

Rated load: 135 KG

Patent

Temperature: from 45 °C to -35 °C

Suspension element: BAND

Area of application:

Facade / Window Cleaning

DIMENSIONS

Size: 1,8m

Weight: 2,15 kg

HARDWARE

Carabiner on anchoring point side:

FS 92

Carabiner on belt side: STAK TRI

MATERIAL

Material:

Polyester, Polyamide, Steel
