

Data sheet

PEANUT I f. Platforms



GENERAL

Art. no.: HSG-021-1,8-8

EAN: 4030281197720

Standard: DIN 19427:2017
EN 360:2002
GS-PS-12:2019
RFU PPE-
R/11.060:2018
RFU PPE-
R/11.085:2018

E-class number: 40-02-01-03

Customs no.: 84798997

Data sheet

PEANUT I f. Platforms

The compact connecting device PEANUT I with the KOBRA TRI karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The small steel trilock karabiner with a breaking load of 45 kN and an opening width of 22 mm is characterised above all by its robustness. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Fall indicator

Suitable for edges: yes

Max. service life: 10 Years

Max. number of persons: 1

Rated load: 135 KG

Patent

Temperature: from 45 °C to -35 °C

Suspension element: BAND

Area of application:

Facade / Window Cleaning

DIMENSIONS

Size: 1,8m

Weight: 1,62 kg

HARDWARE

Carabiner on anchoring point side:

KOBRA TRI

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:

Polyester, Polyamide, Steel
