

Data sheet

PEANUT I



GENERAL

Art. no.:	HSG-021-1,8-9	E-class number:	40-02-01-03
EAN:	4030281294825	Customs no.:	84798997
Standard:	DIN 19427:2017 EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2018		

Data sheet

PEANUT I

The compact connecting device PEANUT I with the RESISTOR karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The RESISTOR is extremely robust and handy and is particularly suitable for quick hooking into the structure. The fastener is edge-suitable and can therefore also be used for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Fall indicator

Suitable for edges:	yes
---------------------	-----

Max. service life:	10 Years
--------------------	----------

Max. number of persons:	1
-------------------------	---

Rated load:	135 KG
-------------	--------

Patent

Temperature:	from 45 °C to -35 °C
--------------	----------------------

Suspension element:	BAND
---------------------	------

Area of application:

Facade / Window Cleaning

DIMENSIONS

Size:	1,8m
-------	------

Weight:	1,36 kg
---------	---------

HARDWARE

Carabiner on anchoring point side:

RESISTOR

Carabiner on belt side: STAK TRI AL

MATERIAL

Material:

Polyester, Polyamide, Steel
