

Data sheet

PEANUT I



GENERAL

Art. no.:	HSG-021-2,5-1	E-class number:	40-02-01-03
EAN:	4030281181910	Customs no.:	84798997
Standard:	EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2018		

Data sheet

PEANUT I

The compact connecting device PEANUT I with FS90 ALU karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The all-rounder carabiner with an opening width of 60 mm is suitable for almost all structures and can be opened easily. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Fall indicator

Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND

Area of application:

Construction / Roofer / Carpenter, Lift
Construction, Power Supplies / -Transmission /
Telecommunications, Scaffolding

DIMENSIONS

Size:	2,5m
Weight:	1,68 kg

HARDWARE

Carabiner on anchoring point side:

FS 90 ALU

Carabiner on belt side: STAK TRI

MATERIAL

Material:

Polyester, Polyamide, Aluminium
