

Data sheet

PEANUT I



GENERAL

Art. no.:	HSG-021-2,5-2	E-class number:	40-02-01-03
EAN:	4030281181972	Customs no.:	84798997
Standard:	EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2018		

Data sheet

PEANUT I

The compact connecting device PEANUT I with FS110 ALU karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The karabiner with an opening width of 110 mm is particularly suitable for large structures. The fastener is suitable for edges and thus also serves for horizontal securing. PEANUT I contains the One-4-All shock absorber and is therefore suitable for a very wide range of user weights from 50 to 135 kg. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Fall indicator

Suitable for edges:	yes
---------------------	-----

Max. service life:	10 Years
--------------------	----------

Max. number of persons:	1
-------------------------	---

Rated load:	135 KG
-------------	--------

Patent

Temperature:	from 45 °C to -35 °C
--------------	----------------------

Suspension element:	BAND
---------------------	------

Area of application:	Scaffolding
----------------------	-------------

DIMENSIONS

Size:	2,5m
-------	------

Weight:	2,19 kg
---------	---------

HARDWARE

Carabiner on anchoring point side:

FS 110 Alu

Carabiner on belt side: STAK TRI

MATERIAL

Material:

Polyester, Polyamide, Aluminium
