

Data sheet

PEANUT I



GENERAL

Art. no.: HSG-021-2,5-3

EAN: 4030281181927

Standard: EN 360:2002
GS-PS-12:2019
RFU PPE-
R/11.060:2018
RFU PPE-
R/11.085:2018

E-class number: 40-02-01-03

Customs no.: 84798997

Data sheet

PEANUT I

The compact connecting device PEANUT I with FS90 ST karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The karabiner with an opening width of 59 cm can be used variably and is extremely robust. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All shock absorber and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Fall indicator

Suitable for edges:	yes
---------------------	-----

Max. service life:	10 Years
--------------------	----------

Max. number of persons:	1
-------------------------	---

Rated load:	135 KG
-------------	--------

Patent

Temperature:	from 45 °C to -35 °C
--------------	----------------------

Suspension element:	BAND
---------------------	------

Area of application:	Scaffolding
----------------------	-------------

DIMENSIONS

Size:	2,5m
-------	------

Weight:	1,85 kg
---------	---------

HARDWARE

Carabiner on anchoring point side:

FS 90 ST

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:

Polyester, Polyamide, Steel
