

Data sheet

PEANUT I



GENERAL

Art. no.:	HSG-021-2,5-4	E-class number:	40-02-01-03
EAN:	4030281181989	Customs no.:	84798997
Standard:	EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2018		



Data sheet

PEANUT I

The compact connecting device PEANUT I with FS90 ANSI karabiners convinces with its selfretracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The steel karabiner with 50 kN is particularly robust due to its reinforced gate. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All shock absorber and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

-	l ın	dia	10 +	~ r
Fal		11 111	.01	()I

Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	Scaffolding

DIMENSIONS

Size:	2,5m
Weight:	2,17 kg



HARDWARE

Carabiner on anchoring point side:

FS 90 ST ANSI

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:

Polyester, Polyamide, Steel