

Data sheet

PEANUT I



GENERAL

Art. no.:	HSG-021-2,5-6	E-class number:	40-02-01-03
EAN:	4030281182009	Customs no.:	84798997
Standard:	EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2018		

Data sheet

PEANUT I

The compact connecting device PEANUT I with the FS64 AL OR karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the drop height is extremely low. The FS64 AL OR GR with an opening width of 64 mm is light and yet very robust with a reinforced gate. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Fall indicator

Suitable for edges:	yes
---------------------	-----

Max. service life:	10 Years
--------------------	----------

Max. number of persons:	1
-------------------------	---

Rated load:	135 KG
-------------	--------

Patent

Temperature:	from 45 °C to -35 °C
--------------	----------------------

Suspension element:	BAND
---------------------	------

Area of application:	Scaffolding
----------------------	-------------

DIMENSIONS

Size:	2,5m
-------	------

Weight:	1,92 kg
---------	---------

HARDWARE

Carabiner on anchoring point side:

FS 64 ALU

Carabiner on belt side: KOBRA AL TRI

MATERIAL

Material:

Polyester, Polyamide, Aluminium
