

## Data sheet

# PEANUT I



## GENERAL

Art. no.: HSG-021-2,5-8

EAN: 4030281294832

Standard: EN 360:2002  
GS-PS-12:2019  
RFU PPE-  
R/11.060:2018  
RFU PPE-  
R/11.085:2018

E-class number: 40-02-01-03

Customs no.: 84798997

## Data sheet

### PEANUT I

The compact connecting device PEANUT I with the RESISTOR karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The RESTISTOR is extremely robust and handy and is particularly suitable for quick hooking into the structure. The fastener is edge-suitable and can therefore also be used for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

#### FEATURES

Fall indicator

---

Suitable for edges:	yes
---------------------	-----

---

Max. service life:	10 Years
--------------------	----------

---

Max. number of persons:	1
-------------------------	---

---

Rated load:	135 KG
-------------	--------

---

Patent

---

Temperature:	from 45 °C to -35 °C
--------------	----------------------

---

Suspension element:	BAND
---------------------	------

---

Area of application:	Scaffolding
----------------------	-------------

---

#### DIMENSIONS

---

Size:	2,5m
-------	------

---

Weight:	1,37 kg
---------	---------

---

## HARDWARE

Carabiner on anchoring point side:

RESISTOR

---

Carabiner on belt side: STAK TRI AL

---

## MATERIAL

Material:

Polyester, Polyamide, Steel

---