

Data sheet

PEANUT Y



GENERAL

Art. no.:	HSG-022-1,8-2	E-class number:	40-02-01-03
EAN:	4030281182030	Customs no.:	84798997
Standard:	BASED ON EN 354:2010 DIN 19427:2017 EN 360:2002 RFU CNB/P/11.060 RFU CNB/P/11.085		

Data sheet

PEANUT Y

The compact connecting device PEANUT Y with FS110 ALU karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the fall height is extremely low. The karabiner with an opening width of 110 mm is particularly suitable for large structures. The lanyard is perfectly suited for continuous, reciprocal securing - even at lower heights. The PEANUT Y is edge-suitable and therefore also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 1.8 m long arms, the PEANUT Y is ideal for securing in aerial work platforms. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap fall arrester has been released and provides additional safety.

FEATURES

Fall indicator

Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	Facade / Window Cleaning, Power Supplies / - Transmission / Telecommunications

DIMENSIONS

Size:	1,8m
Weight:	3,85 kg

HARDWARE

Carabiner on anchoring point side:

FS 110 Alu

Carabiner on belt side: STAK TRI

MATERIAL

Material:

Polyester, Polyamide, Aluminium
