

## Data sheet

# PEANUT Y



## GENERAL

Art. no.:	HSG-022-1,8-6	E-class number:	40-02-01-03
EAN:	4030281182078	Customs no.:	84798997
Standard:	BASED ON EN 354:2010 DIN 19427:2017 EN 360:2002 RFU CNB/P/11.060 RFU CNB/P/11.085		

## Data sheet

### PEANUT Y

The compact connecting device PEANUT Y with the FS64 AL OR karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the drop height is extremely low. The FS64 AL OR GR with an opening width of 64 mm is light and yet very robust with a reinforced gate. The lanyard is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and thus also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 1.8 m long arms, the PEANUT Y is ideal for securing in aerial work platforms. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap fall arrester has been released and provides additional safety.

#### FEATURES

Fall indicator

---

Suitable for edges: yes

---

Max. service life: 10 Years

---

Max. number of persons: 1

---

Rated load: 135 KG

---

Patent

---

Temperature: from 45 °C to -35 °C

---

Suspension element: BAND

---

Area of application:

---

Facade / Window Cleaning, High Rack

#### DIMENSIONS

---

Size: 1,8m

---

Weight: 3,28 kg

---

## HARDWARE

Carabiner on anchoring point side:

FS 64 ALU

---

Carabiner on belt side: KOBRA AL TRI

---

## MATERIAL

Material:

Polyester, Polyamide, Aluminium

---